



## Flange mounted transducer "FMT", maximum torque: 2 Nm



### Order data

Order number	654350 2
GTIN	2050001016669
Item class	66D

### Description

#### Version:

- **Static sensors complete with cable (2 m) for direct connection to No. 654300 or No. 654340 (automatic detection of calibration data).**
- **Direct fixing to the workbench with 3 screws (not included).**

#### Supplied with:

#### **UKAS calibration certificate on the right.**

Up to and including size 150 with screw tightening simulator for checking electric and pneumatic screwdrivers. In a sturdy plastic case.

#### **Note:**

Not suitable for impact wrenches.

Test certificate: Manufacturer's test certificate

Calibration: O4

Measuring range: 0.04 - 2 Nm

Square socket: 1/4 inch

Hexagon socket: 1/4 inch

### Technical description

maximum torque	2 Nm
Square socket	1/4 inch
Measuring range	0.04 - 2 Nm
Hexagon socket	1/4 inch
Calibration	O4

Direction of tightening	Right-hand tightening
Torque measuring accuracy	± 0.5 %
Test certificate	Manufacturer's test certificate

### Services

Calibration Torque analyser / sensor maximum torque 400 Nm	018860 400
Calibration, right Torque analyser / sensor Type 400	020120 400

### Accessories

Screw tightening simulator maximum torque 2 Nm	654352 2
--	----------