



## Electronic torque analyser "ProTest", maximum torque: 60 Nm



### Order data

Order number	654460 60
GTIN	2050001017765
Item class	66D

### Description

#### Version:

- **Sturdy cast aluminium body.**
- **Large-format LCD display.**
- **Easy to use – pictogram keypad for direct choice of the test procedure etc.**
- **User-specific input of target torque with upper and lower tolerances; acoustic and visual signal (3 LEDs) on reaching / exceeding the target torque.**
- **3 user modes: Following, inflection point detection, and peak value display.**

#### Advantage:

- **Checking to DIN EN ISO 6789; only the target value has to be put in – the torque analyser does the rest.**
- **11 display languages.**
- **Testing in horizontal and vertical position.**
- **Display and measured value sensor can be separated.**

#### Application:

For setting and calibrating torque tools.

#### Supplied with:

Measured value sensor, display unit, mains adapter, RS-232C connecting cable to PC or printer, 2 securing screws, and square drive adapter all in a sturdy case, **including UKAS calibration certificate, right-hand.**

#### Note:

Wall bracket under No. 654462.

Calibration: O4

Torque measuring accuracy:  $\pm 0.5\%$

Measuring range: 1.2 - 60 Nm

Display unit width: 185 mm

Display unit height: 128 mm

Display unit depth: 104 mm

Measuring value sensor width: 106 mm

Measuring value sensor height: 100 mm

## Technical description

Display unit depth	104 mm
Measuring value sensor height	100 mm
Display unit width	185 mm
maximum torque	60 Nm
Measuring value sensor depth	185 mm
Measuring range	1.2 - 60 Nm
Display unit height	128 mm
Square drive adapter	1/4; 3/8; 1/2 inch
Measuring value sensor width	106 mm
Weight	6.3 kg
Torque measuring accuracy	$\pm 0.5\%$
Power supply	Mains operated
Direction of tightening	Right-hand tightening
Interface	RS232C interface
Test certificate	Manufacturer's test certificate
Calibration	O4
Type of product	Torque wrenches

## Services

DAkkS calibration Torque analyser / sensor maximum torque 1000/2 Nm

018840 1000/2

Labelling laser-etched Type	018940
Calibration Torque analyser / sensor maximum torque 400 Nm	018860 400
DAkkS calibration Torque analyser / sensor maximum torque 1000 Nm	018840 1000
DAkkS calibration, right Torque analyser / sensor Type 1000	020130 1000
Calibration, right Torque analyser / sensor Type 400	020120 400
DAkkS calibration on both sides Torque analyser / sensor maximum torque 1000/2 Nm	020150 1000/2

### Accessories

Wall bracket for ProTest	654462
Software for monitoring torque wrenches	654270