

**Electronic torque analyser „TruCheck™ 2“, maximum torque: 1100 Nm****Order data**

Order number	654471 1100
GTIN	5060207566520
Item class	66D

Description**Version:**

- **Compact, handy torque analyser.**
- **Screw attachment to a flat surface (table, wall etc.).**
- **LCD display. LED background lighting ensures good legibility under poor lighting conditions.**
- **The integral micro-USB 2.0 port provides the power supply.**
- **Units of measure: N·m.**

Advantage:

- **Very easy to use (reduces errors).**
- **Suitable even for users who are not “Calibration Specialists”.**
- **Only a single push button to zero the display.**

Application:

Setting and testing triggering and indicating torque wrenches.

Accuracy:

Percentage measured value error $\pm 1\%$ for the measurement range 110-1100 N·m; $\pm 2\%$ for the measurement range less than 110 N·m.

Supplied with:

USB power supply unit (EU/UK/US/AUS), micro USB 2.0 cable, in sturdy plastic case.

Calibration: O4

Torque measuring accuracy: $\pm 1\%$

Torque measuring accuracy: $\pm 2\%$
Measuring range: 50 - 1100 Nm
Display unit width: 140 mm
Display unit height: 120 mm
Display unit depth: 132.5 mm
Weight: 3.5 kg
Square drive adapter: 3/4 inch

Technical description

maximum torque	1100 Nm
Measuring range	50 - 1100 Nm
Display unit depth	132.5 mm
Square drive adapter	3/4 inch
Display unit width	140 mm
Weight	3.5 kg
Display unit height	120 mm
Torque measuring accuracy	$\pm 1\%$
Torque measuring accuracy	$\pm 2\%$
Power supply	Mains operated
Nominal voltage	100 - 240 V
External hexagon drive	27 mm
Direction of tightening	Right-hand tightening
Test certificate	Manufacturer's test certificate
Calibration	O4