



## Electronic torque analyser „TruCheck™ 2“, maximum torque: 30 Nm



### Order data

Order number	654471 30
GTIN	5060207566667
Item class	66D

### Description

#### Version:

- **Compact, handy torque analyser.**
- **Screw attachment to a flat surface (table, wall etc.).**
- **LCD display. LED background lighting ensures good legibility under poor lighting conditions.**
- **The integral micro-USB 2.0 port provides the power supply.**
- **Units of measure: N·m.**

#### Advantage:

- **Very easy to use (reduces errors).**
- **Suitable even for users who are not “Calibration Specialists”.**
- **Only a single push button to zero the display.**

#### Application:

Setting and testing triggering and indicating torque wrenches.

#### Accuracy:

Percentage measured value error  $\pm 1\%$ .

#### Supplied with:

USB power supply unit (EU/UK/US/AUS), micro USB 2.0 cable, in sturdy plastic case.

Calibration: O4

Torque measuring accuracy:  $\pm 1\%$

Measuring range: 1.5 - 30 Nm

Display unit width: 175 mm

Display unit height: 64 mm

Display unit depth: 72 mm

Weight: 1.4 kg  
 Square drive adapter: 1/4 inch

## Technical description

Measuring range	1.5 - 30 Nm
Weight	1.4 kg
Torque measuring accuracy	±1 %
Display unit width	175 mm
Square drive adapter	1/4 inch
Square drive adapter	3/8 inch
Display unit height	64 mm
maximum torque	30 Nm
Display unit depth	72 mm
Power supply	Mains operated
Nominal voltage	100 - 240 V
External hexagon drive	10 mm
Direction of tightening	Right-hand tightening
Test certificate	Manufacturer's test certificate
Calibration	O4

## Services

Calibration Torque analyser / sensor maximum torque 400 Nm	018860 400
DAkkS calibration Torque analyser / sensor maximum torque 1000 Nm	018840 1000
Labelling laser-etched Type	018940