



Electronic torque analyser „TruCheck™ 2“, maximum torque: 350 Nm



Order data

Order number	654471 350
GTIN	5060207566506
Item class	66D

Description

Version:

- **Compact, handy torque analyser.**
- **Screw attachment to a flat surface (table, wall etc.).**
- **LCD display. LED background lighting ensures good legibility under poor lighting conditions.**
- **The integral micro-USB 2.0 port provides the power supply.**
- **Units of measure: N·m.**

Advantage:

- **Very easy to use (reduces errors).**
- **Suitable even for users who are not “Calibration Specialists”.**
- **Only a single push button to zero the display.**

Application:

Setting and testing triggering and indicating torque wrenches.

Accuracy:

Percentage measured value error $\pm 1\%$.

Supplied with:

USB power supply unit (EU/UK/US/AUS), micro USB 2.0 cable, in sturdy plastic case.

Calibration: O4

Torque measuring accuracy: $\pm 1\%$

Measuring range: 10 - 350 Nm

Display unit width: 138 mm
 Display unit height: 110 mm
 Display unit depth: 117 mm
 Weight: 2.7 kg
 Square drive adapter: 1/2 inch

Technical description

maximum torque	350 Nm
Measuring range	10 - 350 Nm
Display unit width	138 mm
Display unit height	110 mm
Display unit depth	117 mm
Weight	2.7 kg
Square drive adapter	1/2 inch
Torque measuring accuracy	± 1 %
Power supply	Mains operated
Nominal voltage	100 - 240 V
Direction of tightening	Right-hand tightening
Test certificate	Manufacturer's test certificate
Calibration	O4

Services

Calibration Torque analyser / sensor maximum torque 400 Nm	018860 400
DAkkS calibration Torque analyser / sensor maximum torque 1000 Nm	018840 1000
Labelling laser-etched Type	018940