



## Electronic torque analyser „TruCheck™ 2 Plus“, maximum torque: 350 Nm



### Order data

Order number	654476 350
GTIN	5060207566131
Item class	66D

### Description

#### Version:

- **3 user modes: Tracking display (Track) Trigger point sensing (First Peak) Peak value display (Final-Peak).**
- **Easy input of target torque with tolerances.**
- **LCD display. LED background lighting ensures good legibility under poor lighting conditions.**
- **The integral micro-USB 2.0 port provides the power supply and data transmission.**
- **12 display languages.**
- **Memory for saving up to 15 measured values.**
- **Units of measure: N·m, lbf·ft, lbf·in.**

#### Advantage:

Quick and visually easily recognised status display thanks to change of colour of the display (red, yellow, green). Simple transmission of measured data available via a USB interface.

#### Application:

Setting and testing triggering and indicating torque wrenches.

#### Accuracy:

Percentage measured value error  $\pm 1\%$ .

#### Supplied with:

USB power supply unit (EU/UK/US/AUS), micro USB 2.0 cable, in sturdy plastic case.

Calibration: O4

Torque measuring accuracy:  $\pm 1\%$   
 Measuring range: 10 - 350 Nm  
 Display unit width: 138 mm  
 Display unit height: 110 mm  
 Display unit depth: 117 mm  
 Weight: 2.7 kg  
 Square drive adapter: 1/2 inch

## Technical description

maximum torque	350 Nm
Torque measuring accuracy	$\pm 1\%$
Measuring range	10 - 350 Nm
Weight	2.7 kg
Display unit height	110 mm
Display unit width	138 mm
Square drive adapter	1/2 inch
Display unit depth	117 mm
Power supply	Mains operated
Nominal voltage	100 - 240 V
Direction of tightening	Right-hand tightening
Interface	USB interface
Test certificate	Manufacturer's test certificate
Calibration	O4

## Services

Calibration Torque analyser / sensor maximum torque 400 Nm	018860 400
DAkkS calibration Torque analyser / sensor maximum torque 1000 Nm	018840 1000
Labelling laser-etched Type	018940