



Torque sensor for TTS-2000, maximum torque: 1355 Nm



Order data

Order number	654910 1355
GTIN	856986007065
Item class	66D

Description

Version:

The built-in SMART chip stores the sensor identification, so that all system components are interchangeable. The torque sensor can withstand a mechanical overload up to 150% of the nominal value. On reaching of 110% of nominal value the sensor emits an acoustic warning signal, plus in addition a visual warning appears on the display. The torque sensor is equipped with a durable cable proof against polarity inversion, which can be exchanged if necessary without problems.

Standard:

Vierkantantriebe nach DIN 3120 / ISO1174-1.
 Test certificate: Manufacturer's test certificate
 Torque measuring accuracy: ± 1 %
 Torque measuring accuracy: ± 1 %
 Torque range: 135 - 1355 Nm
 Length: 178 mm
 Diameter: 64 mm
 Cable length: 1.2 m
 Weight: 3.2 kg

Technical description

Cable length	1.2 m
Weight	3.2 kg
Torque measuring accuracy	±1 %
Diameter	64 mm
Torque range	135 - 1355 Nm
Length	178 mm
maximum torque	1355 Nm
Drive square	1 inch
Square drive	1 inch
Direction of tightening	For right and left-hand tightening
Test certificate	Manufacturer's test certificate