



## Torque sensor for TTS-2000, maximum torque: 2711 Nm



### Order data

Order number	654910 2711
GTIN	856986007072
Item class	66D

### Description

#### Version:

The built-in SMART chip stores the sensor identification, so that all system components are interchangeable. The torque sensor can withstand a mechanical overload up to 150% of the nominal value. On reaching of 110% of nominal value the sensor emits an acoustic warning signal, plus in addition a visual warning appears on the display. The torque sensor is equipped with a durable cable proof against polarity inversion, which can be exchanged if necessary without problems.

#### Standard:

Vierkantantriebe nach DIN 3120 / ISO1174-1.

Torque measuring accuracy:  $\pm 1$  %

Torque measuring accuracy:  $\pm 1$  %

Torque range: 271 - 2711 Nm

Length: 178 mm

Diameter: 64 mm

Cable length: 1.2 m

Weight: 3.2 kg

### Technical description

Torque measuring accuracy	±1 %
Weight	3.2 kg
Diameter	64 mm
maximum torque	2711 Nm
Cable length	1.2 m
Length	178 mm
Torque range	271 - 2711 Nm
Drive square	1 inch
Square drive	1 inch
Direction of tightening	For right and left-hand tightening
Test certificate	Manufacturer's test certificate