



## Electronic torque wrench / rotational angle wrench with plug-in ratchet, maximum torque: 400 Nm



### Order data

Order number	655230 400
GTIN	4018754212774
Item class	63A

### Description

#### Version:

Highly precise electronic torque / rotational angle wrench for very reliable screw tightening and checking of screw fastenings. Clear OLED display with colour screen and extremely simple menu navigation. Sturdy wrench with compact housing and sturdy rectangular section shaft. "Direct mode" allows quick general-purpose use. There are up to 200 user-specific screw tightening cases which can be programmed, which can be incorporated in procedural plans. 4 measurement modes: Torque and angle of rotation. Process reliability results achieved by torque with angular monitoring or rotational angle with torque monitoring. Memory capacity for up to 2500 measurements included. Can be programmed by a PC; password protection for security against tampering. Rotary angle measurement can be programmed easily, no reference arm required. Target values and tolerances can be specified. Peak and Track function modes. Integrated automatic reminder of calibration after the number of operations and elapsed time.

**Units of measure:** N·m, lbf·ft, lbf·in.

As well as the functional modes Peak and Track the wrench can also be used in trigger mode. When the set torque or rotational angle is reached the wrench triggers with audible and tactile signals like a conventional mechanical torque wrench.

- **Reversible ratchet**
- **Easy input of pitch settings: For tools with a different pitch setting simply input the new pitch. No laborious calculations with formulae.**
- **QuickRelease: Secure engagement and quick change of plug-in heads.**
- **Data output: The USB interface allows the saved data to be read out and analysed via PC.**
- **Easy to use: All functions can be selected using the arrow keys. Clear and simple menu navigation.**
- **Warning signals: – Acoustic (buzzer) – Visual via 3 LEDs and a colour screen**
- **2-component handle: Resistant to oils, greases, fuels, and Skydrol.**

MANOSKOP® 714 electromechanical rotation angle torque wrench combines the best of two worlds. Users benefit from a precise, electronic measurement, but can also feel and hear the well-known "clicking" of mechanical torque wrenches.

**Standard:**

Geprüft nach DIN EN ISO 6789.

**Supplied with:**

With sturdy plastic case (size 400 in a sturdy sheet metal case) and 4 batteries (1.5 V micro / AAA / LR3), USB data cable, and SENSOMASTER 4 software for transmitting the measured data.

Direction of tightening: For right- and left-hand tightening

Torque measuring accuracy:  $\pm 2$  %

Measuring accuracy rotational angle:  $\pm 1$  %

Measuring accuracy rotational angle:  $\pm 1$  degrees

Exchangeable tool: Plug-in head

Interface: USB interface

Overall length L: 737 mm

Torque range: 40 - 400 Nm

Torque range: 30 - 300 lbfft

Torque range: 360 - 3600 lbfin

Resolution: 0.1 Nm

Weight: 2275 g

## Technical description

Square drive	3/4 inch
maximum torque	400 Nm
Weight	2275 g
Resolution	0.1 Nm
Socket for plug-in head	14×18 mm
Torque measuring accuracy	$\pm 2$ %
Exchangeable tool	Plug-in head
Torque range	40 - 400 Nm
Torque range	30 - 300 lbfft
Number of batteries contained	4
Article no of the battery / rechargeable battery fitted	081557 LR3
Torque range	360 - 3600 lbfin
Series	MANOSKOP® 714R
Trigger principle	mechanical short-travel release

Adjustable trigger value	adjustable
Lever length including factory calibration reference dimension [L <sub>3</sub> ]	681 mm
Feedback	visning
Feedback	udløsning
Overall length L	737 mm
Lever length without plug-in head [L <sub>1</sub> ]	656 mm
Connection format	for plug-in heads (rectangular socket)
Measurement process	Torque
Measurement process	Rotation angle
Reversible reading	Nm
Reversible reading	lbf·in
Reversible reading	lbf·ft
Setting the trigger value	digital, adjustable
Display	digital
Standard	DIN EN ISO 6789
Adjusted reference dimension on the torque wrench [L <sub>2</sub> ]	25 mm
Calibration	O3
Calibration	O5
Calibration	O1
Direction of tightening	For right- and left-hand tightening
Test certificate	Manufacturer's test certificate
Interface	USB interface
Measuring accuracy rotational angle	±1 degrees
Measuring accuracy rotational angle	±1 %
Data can be recorded	yes
Measurement technology	electronic
Release signalling	optisk
Release signalling	acoustic
Power supply	Battery-powered

Type of product	Torque Wrench
-----------------	---------------

## Services

Labelling laser-etched Type	018940
Calibration Torque wrench maximum torque 400 Nm	018820 400
DAkkS calibration Torque wrench maximum torque 1000 Nm	018830 1000

## Accessories

Plug-in ratchet reversible Type-Square drive 2-3/4HD inch	657600 2-3/4HD
Plug-in ratchet reversible Type-Square drive 2-3/4 inch	657600 2-3/4
Plug-in ratchet reversible Type-Square drive 2-1/2 inch	657600 2-1/2
Alkaline manganese battery set International size LR3	081557 LR3
Plug-in ratchet reversible with QuickRelease ejector Type-Square drive 2-1/2 inch	657590 2-1/2
Alkaline manganese battery set International size LR3	081558 LR3
Alkaline-manganese batteries International size LR3	081556 LR3
Alkaline-manganese batteries International size LR3	081551 LR3
Alkaline-manganese batteries International size LR3	081561 LR3