



Electronic torque wrench / rotational angle wrench with plug-in ratchet, maximum torque: 60 Nm



Order data

Order number	655230 60
GTIN	2050002047075
Item class	63A

Description

Version:

Highly precise electronic torque / rotational angle wrench for very reliable screw tightening and checking of screw fastenings. Clear OLED display with colour screen and extremely simple menu navigation. Sturdy wrench with compact housing and sturdy rectangular section shaft. "Direct mode" allows quick general-purpose use. There are up to 200 user-specific screw tightening cases which can be programmed, which can be incorporated in procedural plans. 4 measurement modes: Torque and angle of rotation. Process reliability results achieved by torque with angular monitoring or rotational angle with torque monitoring. Memory capacity for up to 2500 measurements included. Can be programmed by a PC; password protection for security against tampering. Rotary angle measurement can be programmed easily, no reference arm required. Target values and tolerances can be specified. Peak and Track function modes. Integrated automatic reminder of calibration after the number of operations and elapsed time.

Units of measure: N·m, lbf·ft, lbf·in.

As well as the functional modes Peak and Track the wrench can also be used in trigger mode. When the set torque or rotational angle is reached the wrench triggers with audible and tactile signals like a conventional mechanical torque wrench.

- **Reversible ratchet**
- **Easy input of pitch settings: For tools with a different pitch setting simply input the new pitch. No laborious calculations with formulae.**
- **QuickRelease: Secure engagement and quick change of plug-in heads.**
- **Data output: The USB interface allows the saved data to be read out and analysed via PC.**
- **Easy to use: All functions can be selected using the arrow keys. Clear and simple menu navigation.**
- **Warning signals: – Acoustic (buzzer) – Visual via 3 LEDs and a colour screen**
- **2-component handle: Resistant to oils, greases, fuels, and Skydrol.**

MANOSKOP® 714 electromechanical rotation angle torque wrench combines the best of two worlds. Users benefit from a precise, electronic measurement, but can also feel and hear the well-known "clicking" of mechanical torque wrenches.

Standard:

Geprüft nach DIN EN ISO 6789.

Supplied with:

With sturdy plastic case (size 400 in a sturdy sheet metal case) and 4 batteries (1.5 V micro / AAA / LR3), USB data cable, and SENSOMASTER 4 software for transmitting the measured data.

Direction of tightening: For right- and left-hand tightening

Torque measuring accuracy: $\pm 2\%$

Measuring accuracy rotational angle: $\pm 1\%$

Measuring accuracy rotational angle: ± 1 degrees

Exchangeable tool: Plug-in head

Interface: USB interface

Overall length L: 427 mm

Torque range: 6 - 60 Nm

Torque range: 4.5 - 45 lbfft

Torque range: 54 - 540 lbfin

Resolution: 0.1 Nm

Weight: 965 g

Technical description

Socket for plug-in head	9×12 mm
Square drive	3/8 inch
maximum torque	60 Nm
Resolution	0.1 Nm
Weight	965 g
Torque measuring accuracy	$\pm 2\%$
Exchangeable tool	Plug-in head
Torque range	6 - 60 Nm
Torque range	4.5 - 45 lbfft
Article no of the battery / rechargeable battery fitted	081557 LR3
Number of batteries contained	4
Torque range	54 - 540 lbfin
Series	MANOSKOP® 714
Measurement process	Torque

Measurement process	Rotation angle
Overall length L	427 mm
Lever length without plug-in head [I ₁]	355 mm
Adjusted reference dimension on the torque wrench [I ₂]	17.5 mm
Connection format	for plug-in heads (rectangular socket)
Reversible reading	Nm
Reversible reading	lbf·in
Reversible reading	lbf·ft
Display	digital
Standard	DIN EN ISO 6789
Lever length including factory calibration reference dimension [I ₃]	372.5 mm
Feedback	visning
Feedback	udløsning
Setting the trigger value	digital, adjustable
Trigger principle	mechanical short-travel release
Adjustable trigger value	adjustable
Calibration	O3
Calibration	O5
Calibration	O1
Direction of tightening	For right- and left-hand tightening
Test certificate	Manufacturer's test certificate
Interface	USB interface
Measuring accuracy rotational angle	±1 degrees
Measuring accuracy rotational angle	±1 %
Data can be recorded	yes
Measurement technology	electronic
Release signalling	optisk
Release signalling	akustisk
Release signalling	haptisk

Power supply	Battery-powered
Type of product	Torque Wrench

Services

Calibration Torque wrench maximum torque 400 Nm	018820 400
Labelling laser-etched Type	018940

Accessories

Plug-in ratchet reversible with QuickRelease ejector Type-Square drive 1-3/8 inch	657590 1-3/8
Plug-in ratchet reversible Type-Square drive 1-3/8 inch	657600 1-3/8
Alkaline manganese battery set International size LR3	081558 LR3
Plug-in ratchet reversible Type-Square drive 1-1/4 inch	657600 1-1/4
Alkaline-manganese batteries International size LR3	081556 LR3
Plug-in ratchet reversible Type-Square drive 1-1/2 inch	657600 1-1/2
Plug-in ratchet reversible with QuickRelease ejector Type-Square drive 1-1/4 inch	657590 1-1/4
Alkaline manganese battery set International size LR3	081557 LR3
Plug-in ratchet reversible with QuickRelease ejector Type-Square drive 1-1/2 inch	657590 1-1/2
Alkaline-manganese batteries International size LR3	081561 LR3
Alkaline-manganese batteries International size LR3	081551 LR3