



Electromechanical torque wrench, maximum torque: 1000 Nm



Order data

Order number	655290 1000
GTIN	4018754240050
Item class	63A

Description

Version:

Unique electro-mechanical wrench, which combines both the **“displaying”** and **“triggering”** functions in a single device. When the set torque is reached the wrench triggers, with acoustic and tactile signals like a conventional mechanical torque wrench. In addition the value achieved is displayed and can be transferred to a PC. The additional “displaying” mode provides a continuous visual indication to the user of the torque that is being applied. Saves and documents up to 7500 screw tightening events. An automatic key lock prevents accidental changes to the settings. A PIN code can be entered to prevent unauthorised changes to the settings. The wrench offers a very wide measurement range. Integrated automatic reminder of calibration after the number of operations and elapsed time.

Units of measure: N·m, lbf·ft, lbf·in.

- **Easy input of pitch settings: For plug-in heads with a different reference dimension, simply input the new dimension. No laborious calculations with formulae.**
- **QuickRelease: Secure engagement and quick change of plug-in heads.**
- **Robust, compact body.**
- **Tolerance limit settings, shown clearly on a display with colour changes.**
- **Very simple operation; complete use and menu selection with just 4 buttons.**
- **2-component handle, resistant to oils, greases, fuels, brake fluids, and Skydrol.**
- **USB interface for exporting the data.**

Plug-in ratchet with push-through square.

Standard:

Geprüft nach DIN EN ISO 6789.

Supplied with:

Sturdy plastic box (sizes 100 and 200) and sturdy metal box (from size 400) with 2 batteries (1.5 V mignon / AA / LR6).

Optional extras:

USB adapter, cable with latching plug, SENSOMASTER 4 software.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right- and left-hand tightening

Torque measuring accuracy: $\pm 2\%$

Exchangeable tool: Plug-in head

Interface: USB interface

Test certificate: Manufacturer's test certificate

Calibration: O1

Overall length L: 1437 mm

Torque range: 100 - 1000 Nm

Torque range: 74 - 750 lbfft

Torque range: 900 - 9000 lbfin

Adjustment resolution: 1 Nm

Display resolution: 0.1 Nm

Technical description

Weight	6910 g
Socket for plug-in head	22x28 mm
Display resolution	0.1 Nm
Adjustment resolution	1 Nm
maximum torque	1000 Nm
Square drive	3/4 inch
Torque measuring accuracy	$\pm 2\%$
Exchangeable tool	Plug-in head
Torque range	100 - 1000 Nm
Torque range	74 - 750 lbfft
Number of batteries contained	2
Article no of the battery / rechargeable battery fitted	081561 LR6
Torque range	900 - 9000 lbfin
Series	MANOSKOP® 730DR
Trigger principle	mechanical short-travel release
Overall length L	1437 mm
Adjustable trigger value	adjustable
Standard	DIN EN ISO 6789

Reversible reading	Nm
Reversible reading	lbf·in
Reversible reading	lbf·ft
Measurement process	Torque
Setting the trigger value	digital, adjustable
Lever length without plug-in head [l ₁]	1341 mm
Display	digital
Lever length including factory calibration reference dimension [l ₃]	1396 mm
Connection format	for plug-in heads (rectangular socket)
Adjusted reference dimension on the torque wrench [l ₂]	55 mm
Feedback	visning
Feedback	udløsning
Feedback	acoustic signal
Calibration	O1
Direction of tightening	For right- and left-hand tightening
Test certificate	Manufacturer's test certificate
Interface	USB interface
Data can be recorded	yes
Measurement technology	electronic
Release signalling	optisk
Release signalling	akustisk
Release signalling	haptisk
Battery type	Mignon, AA
Power supply	Battery-powered
Quick release/ quick-change function	yes
Type of product	Torque Wrench

Services

018940

Labelling laser-etched Type	
Calibration Torque wrench maximum torque 1000 Nm	018820 1000
DAkkS calibration Torque wrench maximum torque 1000 Nm	018830 1000

Accessories

Alkaline manganese battery set International size LR6	081558 LR6
USB adapter cable and software for No. 655290	655292
Alkaline-manganese batteries International size LR6	081556 LR6
Alkaline manganese battery set International size LR6	081557 LR6
Alkaline-manganese batteries International size LR6	081551 LR6
Alkaline-manganese batteries International size LR6	081561 LR6