



## Electromechanical torque wrench, maximum torque: 200 Nm



### Order data

Order number	655290 200
GTIN	4018754175659
Item class	63A

### Description

#### Version:

Unique electro-mechanical wrench, which combines both the **"displaying"** and **"triggering"** functions in a single device. When the set torque is reached the wrench triggers, with acoustic and tactile signals like a conventional mechanical torque wrench. In addition the value achieved is displayed and can be transferred to a PC. The additional "displaying" mode provides a continuous visual indication to the user of the torque that is being applied. Saves and documents up to 7500 screw tightening events. An automatic key lock prevents accidental changes to the settings. A PIN code can be entered to prevent unauthorised changes to the settings. The wrench offers a very wide measurement range. Integrated automatic reminder of calibration after the number of operations and elapsed time.

**Units of measure:** N·m, lbf·ft, lbf·in.

- **Easy input of pitch settings: For plug-in heads with a different reference dimension, simply input the new dimension. No laborious calculations with formulae.**
- **QuickRelease: Secure engagement and quick change of plug-in heads.**
- **Robust, compact body.**
- **Tolerance limit settings, shown clearly on a display with colour changes.**
- **Very simple operation; complete use and menu selection with just 4 buttons.**
- **2-component handle, resistant to oils, greases, fuels, brake fluids, and Skydrol.**
- **USB interface for exporting the data.**

With reversible plug-in ratchet.

#### Standard:

Geprüft nach DIN EN ISO 6789.

#### Supplied with:

Sturdy plastic box (sizes 100 and 200) and sturdy metal box (from size 400) with 2 batteries (1.5 V mignon / AA / LR6).

#### Optional extras:

USB adapter, cable with latching plug, SENSOMASTER 4 software.

#### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right- and left-hand tightening

Torque measuring accuracy:  $\pm 2\%$

Exchangeable tool: Plug-in head

Interface: USB interface

Test certificate: Manufacturer's test certificate

Calibration: O1

Overall length L: 594 mm

Torque range: 20 - 200 Nm

Torque range: 15 - 150 lbfft

Torque range: 180 - 1800 lbfin

Adjustment resolution: 0.5 Nm

Display resolution: 0.1 Nm

## Technical description

Display resolution	0.1 Nm
Square drive	1/2 inch
maximum torque	200 Nm
Weight	1663 g
Adjustment resolution	0.5 Nm
Socket for plug-in head	14×18 mm
Torque measuring accuracy	$\pm 2\%$
Exchangeable tool	Plug-in head
Torque range	20 - 200 Nm
Torque range	15 - 150 lbfft
Number of batteries contained	2
Article no of the battery / rechargeable battery fitted	081561 LR6
Torque range	180 - 1800 lbfin
Series	MANOSKOP® 730DR
Feedback	visning
Feedback	udløsning
Feedback	acoustic signal
Reversible reading	Nm

Reversible reading	lbf <sub>in</sub>
Reversible reading	lbf <sub>ft</sub>
Lever length without plug-in head [l <sub>1</sub> ]	515 mm
Adjustable trigger value	adjustable
Setting the trigger value	digital, adjustable
Display	digital
Trigger principle	mechanical short-travel release
Connection format	for plug-in heads (rectangular socket)
Standard	DIN EN ISO 6789
Lever length including factory calibration reference dimension [l <sub>3</sub> ]	540 mm
Measurement process	Torque
Adjusted reference dimension on the torque wrench [l <sub>2</sub> ]	25 mm
Overall length L	594 mm
Calibration	O1
Direction of tightening	For right- and left-hand tightening
Test certificate	Manufacturer's test certificate
Interface	USB interface
Data can be recorded	yes
Measurement technology	electronic
Release signalling	optisk
Release signalling	akustisk
Release signalling	haptisk
Battery type	Mignon, AA
Power supply	Battery-powered
Quick release/ quick-change function	yes
Type of product	Torque Wrench

## Services

018940

Labelling laser-etched Type	
Calibration Torque wrench maximum torque 400 Nm	018820 400
DAkkS calibration Torque wrench maximum torque 1000 Nm	018830 1000

### Accessories

Plug-in ratchet reversible with QuickRelease ejector Type-Square drive 2-1/2 inch	657590 2-1/2
Alkaline manganese battery set International size LR6	081557 LR6
Plug-in ratchet reversible Type-Square drive 2-3/4 inch	657600 2-3/4
Plug-in ratchet reversible Type-Square drive 2-3/4HD inch	657600 2-3/4HD
Alkaline-manganese batteries International size LR6	081556 LR6
Plug-in ratchet reversible Type-Square drive 2-1/2 inch	657600 2-1/2
USB adapter cable and software for No. 655290	655292
Alkaline manganese battery set International size LR6	081558 LR6
Alkaline-manganese batteries International size LR6	081561 LR6
Alkaline-manganese batteries International size LR6	081551 LR6