



Electronic torque wrench, maximum torque: 135 Nm



Order data

Order number	655345 135
GTIN	4045197503831
Item class	62E

Description

Version:

Units of measure: N·m, lbf·ft, lbf·in, kgf·m.

Robust torque wrench with impact resistant casing, 2-component handle, large display and reversible ratchet. Easy operation using large input buttons. Visual and acoustic signal indicates achievement of the set torque **visually and audibly**. Two working modes; selectable between peak value display and following display. The working memory can store up to 50 torque settings. Sturdy plug-in ratchet with change-over wheel.

Application:

Torque control; controlled tightening of screws in a single operation or for small batch production.

Standard:

Geprüft nach DIN EN ISO 6789.

Accuracy:

Clockwise $\pm 2\%$, anticlockwise $\pm 3\%$.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy: $\pm 2\%$

Torque measuring accuracy: $\pm 3\%$

Exchangeable tool: Plug-in head

Test certificate: Manufacturer's test certificate

Calibration: O3

Overall length L: 410 mm

Torque range: 27 - 135 Nm

Resolution: 0.1 Nm

Weight: 1570 g

Adjusted reference dimension on the torque wrench [L₂]: 17.5 mm

Square drive: 3/8 inch

Technical description

maximum torque	135 Nm
Resolution	0.1 Nm
Square drive	3/8 inch
Socket for plug-in head	9×12 mm
Weight	1570 g
Torque measuring accuracy	±2 %
Torque measuring accuracy	±3 %
Exchangeable tool	Plug-in head
Torque range	27 - 135 Nm
Number of batteries contained	1
Overall length L	410 mm
Reversible reading	Nm
Reversible reading	lbfft
Reversible reading	lbfin
Reversible reading	kgfm
Connection format	for plug-in heads (rectangular socket)
Lever length without plug-in head [L ₁]	314.2 mm
Feedback	displaying
Trigger principle	mechanical short-travel release
Adjusted reference dimension on the torque wrench [L ₂]	17.5 mm
Adjustable trigger value	adjustable
Display	digital
Setting the trigger value	digital, adjustable
Lever length including factory calibration reference dimension [L ₃]	331.7 mm
Standard	DIN EN ISO 6789
Measurement process	Torque

Calibration	O3
Direction of tightening	For right and left-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	yes
Measurement technology	electronic
Release signalling	optisk
Release signalling	akustisk
Battery type	LR3
Power supply	Battery-powered
Type of product	Torque Wrench

Services

Calibration Torque wrench both ends maximum torque 400/2 Nm	018821 400/2
Labelling laser-etched Type	018940
DAkkS calibration Torque wrench both ends maximum torque 1000/2 Nm	018831 1000/2

Accessories

Battery compartment cover Type 2	655346 2
Plug-in ratchet Square drive 1-1/4 inch	657620 1-1/4
Plug-in ratchet with ejector Type-Square drive 1-1/4 inch	657580 1-1/4
Plug-in ratchet with ejector Type-Square drive 1-1/2 inch	657580 1-1/2
Plug-in ratchet Square drive 1-3/8 inch	657620 1-3/8
Coin-Driver, short Blade length 45 mm	664311 45
Plug-in ratchet with ejector Type-Square drive 1-3/8 inch	657580 1-3/8
Plug-in ratchet Square drive 1-1/2 inch	657620 1-1/2
Alkaline manganese battery set International size LR6	081558 LR6
Coin-Driver Blade length 45 mm	664310 45
Alkaline manganese battery set International size LR6	081557 LR6

Alkaline-manganese batteries International size LR6	081556 LR6
Plug-in ratchet reversible with ejector Type-Square drive 1-3/8 inch	657582 1-3/8
Alkaline-manganese batteries International size LR6	081551 LR6
Plug-in ratchet Type-Square drive 1-3/8 inch	657630 1-3/8
Plug-in ratchet reversible with ejector Type-Square drive 1-1/4 inch	657582 1-1/4
Plug-in ratchet reversible with ejector Type-Square drive 1-1/2 inch	657582 1-1/2
Plug-in ratchet Type-Square drive 1-1/4 inch	657630 1-1/4
Plug-in ratchet Type-Square drive 1-1/2 inch	657630 1-1/2
Alkaline-manganese batteries International size LR6	081561 LR6