



## Torque wrench with dial gauge display, maximum torque: 100 Nm



### Order data

Order number	655500 100
GTIN	4560138443941
Item class	66F

### Description

**Version:**

One-armed; slim design with easily readable dial gauge. Body entirely of steel, chrome-plated with fixed square drive for plug-in heads.

**Units of measure:** N·m.

**Function:**

Actual torque can be read on the gauge whilst working; the final value is held by the memory pointer to be read later.

**Application:**

For controlled single tightening of screws and for controlled measurements.

**Standard:**

Geprüft nach DIN EN ISO 6789.

**Note:**

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy:  $\pm 3\%$

Test certificate: Manufacturer's test certificate

Calibration: O3

Overall length L: 400 mm

Torque range: 10 - 100 Nm

Scale graduation, 1 graduation =: 1 Nm

Weight: 550 g

Square drive: 1/2 inch

### Technical description

Display	analogue
---------	----------

Square drive	1/2 inch
Weight	550 g
maximum torque	100 Nm
Torque measuring accuracy	±3 %
Direction of tightening	For right and left-hand tightening
Scale graduation, 1 graduation =	1 Nm
Torque range	10 - 100 Nm
Standard	DIN EN ISO 6789
Setting the trigger value	Memory pointer
Lever length including factory calibration reference dimension [l <sub>3</sub> ]	310 mm
Adjustable trigger value	ikke justerbart
Reversible reading	Nm
Connection format	Push-through square drive (ratchet)
Overall length L	400 mm
Feedback	displaying
Measurement process	Torque
Calibration	O3
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	haptisk
Deflection function	no
Slipper function	no
Quick release/ quick-change function	no
Memory pointer	yes
Type of product	Torque Wrench

## Services

018821 400/2

Calibration Torque wrench both ends maximum torque 400/2 Nm	
Labelling laser-etched Type	018940
DAkkS calibration Torque wrench both ends maximum torque 1000/2 Nm	018831 1000/2