

Torque wrench with dial gauge display, maximum torque: 1000 Nm



Order data

Order number	655500 1000
GTIN	4560138444269
Item class	66F

Description

Version:

One-armed; slim design with easily readable dial gauge. Body entirely of steel, chrome-plated with fixed square drive for plug-in heads.

Units of measure: N·m.

Function:

Actual torque can be read on the gauge whilst working; the final value is held by the memory pointer to be read later.

Application:

For controlled single tightening of screws and for controlled measurements.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy: ±3 %

Test certificate: Manufacturer's test certificate

Calibration: O3

Overall length L: 1488 mm Torque range: 100 - 1000 Nm

Scale graduation, 1 graduation =: 20 Nm

Weight: 7400 g Square drive: 1 inch

Technical description

Display	analogue
Square drive	1 inch

Weight	7400 g
maximum torque	1000 Nm
Torque measuring accuracy	±3 %
Direction of tightening	For right and left-hand tightening
Scale graduation, 1 graduation =	20 Nm
Torque range	100 - 1000 Nm
Lever length including factory calibration reference dimension $[I_3]$	1350 mm
Measurement process	Torque
Setting the trigger value	Memory pointer
Connection format	Push-through square drive (ratchet)
Reversible reading	Nm
Standard	DIN EN ISO 6789
Overall length L	1488 mm
Feedback	displaying
Adjustable trigger value	ikke justerbart
Calibration	O3
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	haptisk
Measurement technology	mechanical
Deflection function	no
Slipper function	no
Quick release/ quick-change function	no
Memory pointer	yes
Type of product	Torque Wrench
Services	

1000/2 Nm

Calibration Torque wrench both ends maximum torque

018821 1000/2

Labelling laser-etched Type	018940
DAkkS calibration Torque wrench both ends maximum torque 1000/2 Nm	018831 1000/2