# Your Torque Partner

# Torque wrench with dial gauge display, maximum torque: 1400 Nm

### Order data

Order number	655500 1400
GTIN	2050001017024
Item class	66F

## Description

#### Version:

One-armed; slim design with easily readable dial gauge. Body entirely of steel, chrome-plated with fixed square drive for plug-in heads.

### Units of measure: N·m.

#### Function:

Actual torque can be read on the gauge whilst working; the final value is held by the memory pointer to be read later.

#### **Application:**

For controlled single tightening of screws and for controlled measurements.

#### Standard:

Geprüft nach DIN EN ISO 6789.

#### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy: ±3 %

Test certificate: Manufacturer's test certificate

#### Calibration: O3

Overall length L: 1740 mm Torque range: 200 - 1400 Nm Scale graduation, 1 graduation =: 20 Nm Weight: 9800 g Square drive: 1 inch

## **Technical description**

Weight	9800 g
maximum torque	1400 Nm

© Hoffmann GmbH Qualitätswerkzeuge

Square drive	1 inch
Display	analogue
Torque measuring accuracy	±3 %
Direction of tightening	For right and left-hand tightening
Scale graduation, 1 graduation =	20 Nm
Torque range	200 - 1400 Nm
Connection format	Push-through square drive (ratchet)
Feedback	displaying
Standard	DIN EN ISO 6789
Lever length including factory calibration reference dimension $[I_3]$	1600 mm
Overall length L	1740 mm
Adjustable trigger value	ikke justerbart
Reversible reading	Nm
Setting the trigger value	Memory pointer
Measurement process	Torque
Calibration	03
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	haptisk
Measurement technology	mechanical
Deflection function	no
Slipper function	no
Quick release/ quick-change function	no
Memory pointer	yes
Type of product	Torque Wrench
Comisso	

# Services

Labelling laser-etched Type	018940
-----------------------------	--------