



## Torque wrench with dial gauge display, maximum torque: 2100 Nm



### Order data

Order number	655500 2100
GTIN	2050001017031
Item class	66F

### Description

#### Version:

One-armed; slim design with easily readable dial gauge. Body entirely of steel, chrome-plated with fixed square drive for plug-in heads.

**Units of measure:** N·m.

#### Function:

Actual torque can be read on the gauge whilst working; the final value is held by the memory pointer to be read later.

#### Application:

For controlled single tightening of screws and for controlled measurements.

#### Standard:

Geprüft nach DIN EN ISO 6789.

#### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy:  $\pm 3\%$

Test certificate: Manufacturer's test certificate

Calibration: O3

Overall length L: 2140 mm

Torque range: 200 - 2100 Nm

Scale graduation, 1 graduation =: 20 Nm

Weight: 12000 g

Square drive: 1 inch

### Technical description

Weight	12000 g
maximum torque	2100 Nm

Display	analogue
Square drive	1 inch
Torque measuring accuracy	±3 %
Direction of tightening	For right and left-hand tightening
Scale graduation, 1 graduation =	20 Nm
Torque range	200 - 2100 Nm
Setting the trigger value	Memory pointer
Lever length including factory calibration reference dimension [l <sub>3</sub> ]	2000 mm
Standard	DIN EN ISO 6789
Overall length L	2140 mm
Reversible reading	Nm
Feedback	displaying
Measurement process	Torque
Connection format	Push-through square drive (ratchet)
Adjustable trigger value	ikke justerbart
Calibration	O3
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	haptisk
Measurement technology	mechanical
Deflection function	no
Slipper function	no
Quick release/ quick-change function	no
Memory pointer	yes
Type of product	Torque Wrench

## Services

Labelling laser-etched Type	018940
-----------------------------	--------

