# Your Torque Partner

### Torque wrench with dial gauge display, maximum torque: 280 Nm



## Order data

Order number	655500 280
GTIN	4571141274927
Item class	66F

### Description

#### Version:

One-armed; slim design with easily readable dial gauge. Body entirely of steel, chrome-plated with fixed square drive for plug-in heads.

### Units of measure: N·m.

#### **Function:**

Actual torque can be read on the gauge whilst working; the final value is held by the memory pointer to be read later.

#### **Application:**

For controlled single tightening of screws and for controlled measurements.

#### Standard:

Geprüft nach DIN EN ISO 6789.

### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy: ±3 %

Test certificate: Manufacturer's test certificate

Calibration: O3

Overall length L: 691 mm

Torque range: 30 - 280 Nm

Scale graduation, 1 graduation =: 5 Nm

Weight: 1650 g

Square drive: 1/2 inch

## **Technical description**

#### Square drive

1/2 inch

© Hoffmann GmbH Qualitätswerkzeuge

22.01.202122:39

maximum torque	280 Nm
Weight	1650 g
Display	analogue
Torque measuring accuracy	±3 %
Direction of tightening	For right and left-hand tightening
Scale graduation, 1 graduation =	5 Nm
Torque range	30 - 280 Nm
Standard	DIN EN ISO 6789
Adjustable trigger value	ikke justerbart
Connection format	Push-through square drive (ratchet)
Lever length including factory calibration reference dimension [I <sub>3</sub> ]	600 mm
Overall length L	691 mm
Reversible reading	Nm
Setting the trigger value	Memory pointer
Feedback	displaying
Measurement process	Torque
Calibration	O3
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	haptisk
Deflection function	no
Slipper function	no
Quick release/ quick-change function	no
Memory pointer	yes
Type of product	Torque Wrench

# Services

018821 400/2

© Hoffmann GmbH Qualitätswerkzeuge

Calibration Torque wrench both ends maximum torque 400/2 Nm	
Labelling laser-etched Type	018940
DAkkS calibration Torque wrench both ends maximum torque 1000/2 Nm	018831 1000/2