

Torque wrench with dial gauge display, maximum torque: 3 Nm



Order data

Order number	655500 3
GTIN	4562135127121
Item class	66F

Description

Version:

One-armed; slim design with easily readable dial gauge. Body entirely of steel, chrome-plated with fixed square drive for plug-in heads.

Units of measure: N·m.

Function:

Actual torque can be read on the gauge whilst working; the final value is held by the memory pointer to be read later.

Application:

For controlled single tightening of screws and for controlled measurements.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy: ±3 %

Test certificate: Manufacturer's test certificate

Calibration: 03

Overall length L: 205 mm Torque range: 0.3 - 3 Nm

Scale graduation, 1 graduation =: 0.05 Nm

Weight: 330 g

Square drive: 1/4 inch

Technical description

Connection format	fixed
Direction of tightening	For right and left-hand tightening
Reversible reading	Nm
Head height h	63 mm
Overall length L	205 mm
Lever length including factory calibration reference dimension $\left[I_3\right]$	170 mm
Torque range	0.3 - 3 Nm
Calibration	03
Standard	DIN EN ISO 6789
Display	analogue
Measurement technology	mechanical
Adjustable trigger value	non-adjustable
Head width b	37 mm
maximum torque	3 Nm
Torque measuring accuracy	±3 %
Weight	330 g
Square drive	1/4 inch
Release signalling	visual
Setting the trigger value	Memory pointer
Measurement process	Torque
Data can be recorded	no
Test certificate	Manufacturer's test certificate
Scale graduation, 1 graduation =	0.05 Nm
Feedback	displaying
Deflection function	no
Slipper function	no
Quick release/ quick-change function	no
Memory pointer	yes

Type of product	Torque Wrench	
Services		
Labelling laser-etched Type	018940	
Calibration Torque wrench both ends maximum torque 400/2 Nm	018821 400/2	