

## Torque wrench with dial gauge display, maximum torque: 420 Nm



#### **Order data**

Order number	655500 420
GTIN	4560138442319
Item class	66F

### **Description**

#### **Version:**

One-armed; slim design with easily readable dial gauge. Body entirely of steel, chrome-plated with fixed square drive for plug-in heads.

Units of measure: N·m.

#### **Function:**

Actual torque can be read on the gauge whilst working; the final value is held by the memory pointer to be read later.

#### **Application:**

For controlled single tightening of screws and for controlled measurements.

#### **Standard:**

Geprüft nach DIN EN ISO 6789.

#### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy: ±3 %

Test certificate: Manufacturer's test certificate

Calibration: O3

Overall length L: 890 mm Torque range: 40 - 420 Nm

Scale graduation, 1 graduation =: 5 Nm

Weight: 2400 g

Square drive: 3/4 inch

## **Technical description**

Display analogue

Square drive	3/4 inch
Weight	2400 g
maximum torque	420 Nm
Torque measuring accuracy	±3 %
Direction of tightening	For right and left-hand tightening
Scale graduation, 1 graduation =	5 Nm
Torque range	40 - 420 Nm
Overall length L	890 mm
Adjustable trigger value	ikke justerbart
Feedback	displaying
Lever length including factory calibration reference dimension $\left[I_3\right]$	800 mm
Measurement process	Torque
Connection format	Push-through square drive (ratchet)
Setting the trigger value	Memory pointer
Standard	DIN EN ISO 6789
Reversible reading	Nm
Calibration	O3
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	haptisk
Measurement technology	mechanical
Deflection function	no
Slipper function	no
Quick release/ quick-change function	no
Memory pointer	yes
Type of product	Torque Wrench

# **Services**

018940

Labelling laser-etched Type	
DAkkS calibration Torque wrench both ends maximum torque 1000/2 Nm	018831 1000/2
Calibration Torque wrench both ends maximum torque 1000/2 Nm	018821 1000/2