

**Torque wrench with dial gauge display, maximum torque: 6 Nm****Order data**

Order number	655500 6
GTIN	4562135127169
Item class	66F

**Description****Version:**

One-armed; slim design with easily readable dial gauge. Body entirely of steel, chrome-plated with fixed square drive for plug-in heads.

**Units of measure:** N·m.

**Function:**

Actual torque can be read on the gauge whilst working; the final value is held by the memory pointer to be read later.

**Application:**

For controlled single tightening of screws and for controlled measurements.

**Standard:**

Geprüft nach DIN EN ISO 6789.

**Note:**

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy:  $\pm 3\%$

Test certificate: Manufacturer's test certificate

Calibration: O3

Overall length L: 225 mm

Torque range: 0.6 - 6 Nm

Scale graduation, 1 graduation =: 0.1 Nm

Weight: 330 g

Square drive: 1/4 inch

**Technical description**

maximum torque	6 Nm
Weight	330 g
Square drive	1/4 inch
Display	analogue
Torque measuring accuracy	±3 %
Direction of tightening	For right and left-hand tightening
Scale graduation, 1 graduation =	0.1 Nm
Torque range	0.6 - 6 Nm
Lever length including factory calibration reference dimension [l <sub>3</sub> ]	170 mm
Connection format	Push-through square drive (ratchet)
Adjustable trigger value	ikke justerbart
Setting the trigger value	Memory pointer
Overall length L	225 mm
Feedback	displaying
Standard	DIN EN ISO 6789
Measurement process	Torque
Reversible reading	Nm
Calibration	O3
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	visual
Deflection function	no
Slipper function	no
Quick release/ quick-change function	no
Memory pointer	yes
Type of product	Torque Wrench

## Services

Calibration Torque wrench both ends maximum torque  
400/2 Nm

018821 400/2

Labelling laser-etched Type

018940