



Torque wrench with dial gauge display, maximum torque: 12 Nm



Order data

Order number	655520 12
GTIN	4045197549914
Item class	62E

Description

Version:

One-armed; slim design with easily readable dial gauge. Body entirely of steel, chrome-plated with fixed square drive for plug-in heads.

Units of measure: N·m Non-slip 2-component handle.

Function:

Actual torque can be read on the gauge whilst working; the final value is held by the memory pointer to be read later.

Application:

For controlled single tightening of screws and for controlled measurements.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy: $\pm 4\%$

Test certificate: Manufacturer's test certificate

Calibration: O3

Overall length L: 225 mm

Torque range: 2.4 - 12 Nm

Scale graduation, 1 graduation =: 0.2 Nm

Weight: 400 g

Square drive: 1/4 inch

Technical description

Square drive	1/4 inch
--------------	----------

Display	analogue
Weight	400 g
maximum torque	12 Nm
Torque measuring accuracy	±4 %
Direction of tightening	For right and left-hand tightening
Scale graduation, 1 graduation =	0.2 Nm
Torque range	2.4 - 12 Nm
Measurement process	Torque
Lever length without plug-in head [I ₁]	144 mm
Connection format	Push-through square drive (ratchet)
Lever length including factory calibration reference dimension [I ₃]	180 mm
Overall length L	225 mm
Reversible reading	Nm
Feedback	displaying
Setting the trigger value	Memory pointer
Standard	DIN EN ISO 6789
Adjustable trigger value	non-adjustable
Calibration	O3
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	optisk
Measurement technology	mechanical
Type of product	Torque Wrench

Services

Calibration Torque wrench both ends maximum torque 400/2 Nm	018821 400/2
Labelling laser-etched Type	018940

