

**Torque wrench with dial gauge display, maximum torque: 25 Nm****Order data**

Order number	655520 25
GTIN	4045197549921
Item class	62E

Description**Version:**

One-armed; slim design with easily readable dial gauge. Body entirely of steel, chrome-plated with fixed square drive for plug-in heads.

Units of measure: N·m Non-slip 2-component handle.

Function:

Actual torque can be read on the gauge whilst working; the final value is held by the memory pointer to be read later.

Application:

For controlled single tightening of screws and for controlled measurements.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy: $\pm 4\%$

Test certificate: Manufacturer's test certificate

Calibration: O3

Overall length L: 250 mm

Torque range: 5 - 25 Nm

Scale graduation, 1 graduation =: 0.5 Nm

Weight: 400 g

Square drive: 1/4 inch

Technical description

Square drive	1/4 inch
--------------	----------

maximum torque	25 Nm
Weight	400 g
Display	analogue
Torque measuring accuracy	±4 %
Direction of tightening	For right and left-hand tightening
Scale graduation, 1 graduation =	0.5 Nm
Torque range	5 - 25 Nm
Overall length L	250 mm
Measurement process	Torque
Setting the trigger value	Memory pointer
Reversible reading	Nm
Standard	DIN EN ISO 6789
Adjustable trigger value	non-adjustable
Feedback	displaying
Lever length without plug-in head [I ₁]	164 mm
Lever length including factory calibration reference dimension [I ₃]	200 mm
Connection format	Push-through square drive (ratchet)
Calibration	O3
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	optisk
Measurement technology	mechanical
Type of product	Torque Wrench

Services

Calibration Torque wrench both ends maximum torque 400/2 Nm	018821 400/2
Labelling laser-etched Type	018940

