



## Torque wrench with dial gauge display, maximum torque: 50 Nm



### Order data

Order number	65520 50
GTIN	4045197549938
Item class	62E

### Description

#### Version:

One-armed; slim design with easily readable dial gauge. Body entirely of steel, chrome-plated with fixed square drive for plug-in heads.

**Units of measure:** N·m Non-slip 2-component handle.

#### Function:

Actual torque can be read on the gauge whilst working; the final value is held by the memory pointer to be read later.

#### Application:

For controlled single tightening of screws and for controlled measurements.

#### Standard:

Geprüft nach DIN EN ISO 6789.

#### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy:  $\pm 4\%$

Test certificate: Manufacturer's test certificate

Calibration: O3

Overall length L: 332 mm

Torque range: 10 - 50 Nm

Scale graduation, 1 graduation =: 0.5 Nm

Weight: 600 g

Square drive: 3/8 inch

### Technical description

Weight	600 g
--------	-------

maximum torque	50 Nm
Display	analogue
Square drive	3/8 inch
Torque measuring accuracy	±4 %
Direction of tightening	For right and left-hand tightening
Scale graduation, 1 graduation =	0.5 Nm
Torque range	10 - 50 Nm
Connection format	Push-through square drive (ratchet)
Lever length without plug-in head [L <sub>1</sub> ]	221 mm
Overall length L	332 mm
Feedback	displaying
Setting the trigger value	Memory pointer
Lever length including factory calibration reference dimension [L <sub>3</sub> ]	257 mm
Standard	DIN EN ISO 6789
Reversible reading	Nm
Adjustable trigger value	non-adjustable
Measurement process	Torque
Calibration	O3
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	optisk
Type of product	Torque Wrench

## Services

Calibration Torque wrench both ends maximum torque 400/2 Nm	018821 400/2
Labelling laser-etched Type	018940

