

Torque wrench with reversible ratchet, maximum torque: 500 Nm



Order data

| Order number | 656050 500 |
|--------------|---------------|
| GTIN | 4045197542519 |
| Item class | 61E |

Description

Version:

Handy and very compact single-arm torque wrench, adjustable by scale and self-triggering. Extremely high repeat accuracy, since high quality materials are used throughout. Wearing parts, such as compression springs, are specially pre-treated and sorted. Reversible ratchet for left-hand and right-hand tightening.

Acoustic and perceptible "click effect" ensures particularly easy use and accurate setting of the desired torque.

With built-in reversible ratchet with ejector – for left-hand and right-hand tightening.

Units of measure: N·m

Function:

The wrench triggers giving a "signal" (clearly audible acoustic tone and noticeable vibration) and afterwards is immediately ready for use again.

Application:

For medium to larger batch productions.

Standard:

Geprüft nach DIN EN ISO 6789.

Accuracy:

Of the displayed value only for right-hand tightening: ±3 %

Note:

DAkkS calibration option.

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy: ±3 %

Test certificate: Manufacturer's test certificate

Calibration: 01

Overall length L: 1021 mm

Torque range: 200 - 500 Nm

Scale graduation, 1 graduation =: 2.5 Nm

Weight: 5500 g Square drive: 3/4 inch

Technical description

| | FOO No. |
|---|-------------------------------------|
| maximum torque | 500 Nm |
| Display | analogue |
| Weight | 5500 g |
| Square drive | 3/4 inch |
| Torque measuring accuracy | ±3 % |
| Direction of tightening | For right and left-hand tightening |
| Scale graduation, 1 graduation = | 2.5 Nm |
| Torque range | 200 - 500 Nm |
| Connection format | Push-through square drive (ratchet) |
| Overall length L | 1021 mm |
| Setting the trigger value | with adjustment scale |
| Reversible reading | Nm |
| Trigger principle | mechanical short-travel release |
| Adjustable trigger value | adjustable |
| Lever length including factory calibration reference dimension $\left[I_3\right]$ | 900 mm |
| Measurement process | Torque |
| Feedback | triggering |
| Standard | DIN EN ISO 6789 |
| Calibration | 01 |
| Test certificate | Manufacturer's test certificate |
| Data can be recorded | no |
| Release signalling | akustisk |
| Release signalling | haptisk |
| Measurement technology | mechanical |
| | |



| Type of product | Torque Wrench | |
|---|---------------|--|
| Services | | |
| Labelling laser-etched Type | 018940 | |
| Calibration Torque wrench maximum torque 1000 Nm | 018820 1000 | |
| DAkkS calibration Torque wrench maximum torque 1000 Nm | 018830 1000 | |
| Accessories | | |
| Spare parts set for ratchet Square drive 3/4 inch | 656051 3/4 | |