

Garant**Torque wrench base unit without plug-in head, maximum torque: 320 Nm****Order data**

Order number	656055 320
GTIN	4045197302298
Item class	61E

Description**Version:**

Handy and very compact single-arm torque wrench, adjustable by scale and self-triggering. Extremely high repeat accuracy, since high quality materials are used throughout. Wearing parts, such as compression springs, are specially pre-treated and sorted. Reversible ratchet for left-hand and right-hand tightening.

Acoustic and perceptible "click effect" ensures particularly easy use and accurate setting of the desired torque.

Basic tool with **square plug-in socket** (without plug-in head). Suitable spare jaws No. 657582 - 657950.

Units of measure: N·m

Function:

The wrench triggers giving a "signal" (clearly audible acoustic tone and noticeable vibration) and afterwards is immediately ready for use again.

Application:

For medium to larger batch productions.

Standard:

Geprüft nach DIN EN ISO 6789.

Accuracy:

Of the displayed value **only for right-hand tightening:** $\pm 3 \%$

Note:

DAkkS calibration option.

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy: $\pm 3 \%$

Exchangeable tool: Plug-in head

Test certificate: Manufacturer's test certificate

Calibration: O1
 Overall length L: 596 mm
 Torque range: 60 - 320 Nm
 Scale graduation, 1 graduation =: 2 Nm
 Adjusted reference dimension on the torque wrench [l₂]: 25 mm
 Socket for plug-in head: 14×18 mm

Technical description

maximum torque	320 Nm
Display	analogue
Socket for plug-in head	14×18 mm
Torque measuring accuracy	±3 %
Direction of tightening	For right and left-hand tightening
Exchangeable tool	Plug-in head
Scale graduation, 1 graduation =	2 Nm
Torque range	60 - 320 Nm
Setting the trigger value	with adjustment scale
Reversible reading	Nm
Measurement process	Torque
Trigger principle	mechanical short-travel release
Feedback	triggering
Adjusted reference dimension on the torque wrench [l ₂]	25 mm
Lever length without plug-in head [l ₁]	524 mm
Lever length including factory calibration reference dimension [l ₃]	549 mm
Adjustable trigger value	adjustable
Connection format	for plug-in heads (rectangular socket)
Standard	DIN EN ISO 6789
Overall length L	596 mm
Calibration	O1
Test certificate	Manufacturer's test certificate

Data can be recorded	no
Release signalling	akustisk
Release signalling	haptisk
Measurement technology	mechanical
Type of product	Torque Wrench

Services

Labelling laser-etched Type	018940
Calibration Torque wrench maximum torque 400 Nm	018820 400
DAkkS calibration Torque wrench maximum torque 1000 Nm	018830 1000

Accessories

Plug-in ratchet Square drive 2-3/4 inch	657620 2-3/4
Plug-in ratchet Square drive 2-1/2 inch	657620 2-1/2
Plug-in ratchet with ejector Type-Square drive 2-1/2 inch	657580 2-1/2
Plug-in ratchet reversible with ejector Type-Square drive 2-1/2 inch	657582 2-1/2
Plug-in ratchet Type-Square drive 2-3/4 inch	657630 2-3/4
Plug-in ratchet Type-Square drive 2-1/2 inch	657630 2-1/2