



Torque wrench set, maximum torque: 200 Nm



Order data

Order number	656300 200
GTIN	4013288204691
Item class	63F

Description

Version:

Very sturdy single-handed torque wrench (square drive 1/2 inch) with ergonomic 2-component handle and reversible ratchet for easy adjustment and locking the specified value. Sturdy trigger mechanism ensures clearly audible and sensed response on reaching the set torque. Easy adjustment and locking of the desired torque value, due to display with main scale and fine scale. For right-handed use.

Units of measure: N·m, lbf·ft.

Accuracy:

Tested to DIN EN ISO 6789.

Content:

Hexagon sockets: 1 pc. each size 10; 13; 17; 19 mm

Hexagon screwdriver bits: 1 pc. each 6; 8; 10 mm

Screwdriver bits for Torx®: 1 pc. each TX30; TX40; TX45; TX50

Extension: 1 pc. 125 mm

"Click-Torque" torque wrench: 1 pc. 40-200 Nm

Presented in: Textile box

Square drive: 1/2 inch

Direction of tightening: Right-hand tightening

Torque measuring accuracy: $\pm 3\%$

Test certificate: Manufacturer's test certificate

Calibration: O1
 Standard: DIN EN ISO 6789
 Overall length L: 510 mm
 Torque range: 40 - 200 Nm
 Scale graduation, 1 graduation =: 100 cNm

Technical description

maximum torque	200 cNm
Torque range	40 - 200 Nm
Scale graduation, 1 graduation =	100 cNm
Width across flats range, hexagon wrenches	6-10 mm
Width across flats range, hexagon sockets	10-19 mm
Drive profile	Hexagon screwdriver
Drive profile	Hexagon sockets
Drive profile	Screwdriver for TORX® screws
Calibration	O1
Square drive	1/2 inch
Release signalling	acoustic
Release signalling	haptisk
Test certificate	Manufacturer's test certificate
Measurement technology	mechanical
Torque measuring accuracy	±3 %
Direction of tightening	Right-hand tightening
Reversible reading	lbfft
Reversible reading	lbfft
Data can be recorded	no
Connection format	Push-through square drive (ratchet)
Adjustable trigger value	adjustable
Setting the trigger value	with adjustment scale
Trigger principle	mechanical short-travel release
Feedback	triggering

Display	analogue
Overall length L	510 mm
Measurement process	Torque
Standard	DIN EN ISO 6789
Series	Click-Torque
Scale graduation, 1 graduation =	1 Nm
Torque range	30 - 146 lbfft
Torque fixed setting	no
Type of product	Torque screwdriver