HAZET

Torque wrench with reversible ratchet, maximum torque: 320 Nm

Order data

| Order number | 656500 320 |
|--------------|---------------|
| GTIN | 4000896025367 |
| Item class | 630 |

Description

Version:

Handy and very compact single-arm torque wrench, adjustable by scale and self-triggering. Extremely high repeat accuracy, since high quality materials are used throughout. Wearing parts, such as compression springs, are specially pre-treated and sorted. Reversible ratchet for left-hand and right-hand tightening.

With built-in **reversible ratchet – for left and right hand tightening.**

Units of measure: N·m

Function:

The wrench triggers giving a "signal" (clearly audible acoustic tone and noticeable vibration) and afterwards is immediately ready for use again.

Application:

For medium to larger batch productions.

Standard:

Geprüft nach DIN EN ISO 6789.

Accuracy:

Of the displayed value **only for right-hand tightening:** ± 2 %.

Note:

DAkkS calibration option.

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy: ±2 %

Test certificate: Manufacturer's test certificate

Calibration: O1

Overall length L: 659 mm

Torque range: 60 - 320 Nm

Scale graduation, 1 graduation =: 2 Nm

Weight: 2300 g

Square drive: 1/2 inch

Technical description

| 320 Nm analogue 2300 g 1/2 inch ±2 % nd left-hand tightening 2 Nm |
|---|
| 2300 g 1/2 inch ±2 % nd left-hand tightening 2 Nm |
| 1/2 inch ±2 % nd left-hand tightening 2 Nm |
| ±2 % nd left-hand tightening 2 Nm |
| nd left-hand tightening 2 Nm |
| 2 Nm |
| |
| |
| 60 - 320 Nm |
| adjustment scale |
| adjustable |
| Nm |
| 659 mm |
| 566 mm |
| Torque |
| triggering |
| IN EN ISO 6789 |
| gh square drive (ratchet) |
| cal short-travel release |
| O1 |
| cturer's test certificate |
| no |
| mechanical |
| akustisk |
| haptisk |
| optisk |
| orque Wrench |
| |

© Hoffmann GmbH Qualitätswerkzeuge

Data sheet

Services

| Labelling laser-etched Type | 018940 |
|---|-------------|
| Calibration Torque wrench maximum torque 400 Nm | 018820 400 |
| DAkkS calibration Torque wrench maximum torque 1000 Nm | 018830 1000 |