GEDORE

DREMOMETER[®] torque wrench with fixed square drive, maximum torque: 300 Nm



Order data

Order number	657000 300
GTIN	4002805856215
Item class	63L

Description

Version:

Handy, robust construction, light weight. All heavily loaded parts high-quality steel. **Fixed square drive** (no ratchet). **Units of measure:** N·m, lbf·ft.

Square drive with push-button unlocking.

Function:

On reaching the set torque value the wrench triggers giving a "signal" (acoustic and perceptible) and is then immediately ready for use again.

The desired torque is set using a captive hexagon L-wrench that is pulled out from the end of the handle. The set torque can be easily read on the scale. No inadvertent changes to the setting can be made whilst working.

Application:

For medium to larger series production.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy: ±3 %

Test certificate: Manufacturer's test certificate

Calibration: O1

Overall length L: 617 mm

Torque range: 60 - 300 Nm

Torque range: 45 - 220 lbfft

Scale graduation, 1 graduation =: 5 Nm

Weight: 2000 g

Square drive: 1/2 inch

Technical description

300 Nm
analogue
1/2 inch
2000 g
±3 %
Right-hand tightening
5 Nm
60 - 300 Nm
45 - 220 lbfft
529 mm
Push-through square drive (ratchet)
529 mm
Torque
adjustable
617 mm
Nm
lbfft
DIN EN ISO 6789
with adjustment scale
mechanical short-travel release
triggering
01
Manufacturer's test certificate
no
acoustic
haptisk
mechanical

Series	DREMOMETER®	
Type of product	Torque Wrench	
Services		
Calibration Torque wrench maximum torque 400 Nm	018820 400	
Labelling laser-etched Type	018940	
DAkkS calibration Torque wrench maximum torque 1000 Nm	018830 1000	