



## Torque wrench QuickSelect with plug-in ratchet, maximum torque: 650 Nm



### Order data

Order number	657090 650
GTIN	2050001019776
Item class	63A

### Description

#### Version:

Sturdy compact one-armed torque wrench, adjustable to scale and self-triggering. The accuracy is sustained for many thousands of operations, because high quality material is used for all wearing parts with stressed parts loaded only briefly on each occasion. Body and handle are of sturdy square section. Scales adjustable. **Anti-clockwise tightening by pushing through the drive shank** With **plug-in reversible ratchet**.

**Units of measure:** N·m, lbf·ft.

#### Advantage:

- **Ergonomically shaped two-component handle, resistant to aggressive liquids such as fuel, Skydrol etc.**
- **The adjustment scale is placed behind a sight glass for protection against dirt and damage.**
- **Quick, precise, and reliable setting: Pull the setting knob, "Twist" to set the desired value and "Press" to save it. Setting knob moves easily since there is no spring pressure to be overcome.**

#### Function:

If the set value is reached while using the wrench, the wrench triggers giving a "signal" (acoustic and perceptible) and is then immediately ready for use again.

#### Application:

Since the set torque can be varied, it is ideal for repairs and short series production.

#### Standard:

Geprüft nach DIN EN ISO 6789.

#### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy:  $\pm 3\%$

Exchangeable tool: Plug-in head  
 Test certificate: Manufacturer's test certificate  
 Calibration: O1  
 Torque range: 130 - 650 Nm  
 Torque range: 100 - 480 lbfft  
 Scale graduation, 1 graduation =: 2.5 Nm  
 Weight: 3400 g  
 Adjusted reference dimension on the torque wrench [I<sub>2</sub>]: 25 mm  
 Square drive: 3/4 inch

## Technical description

Square drive	3/4 inch
Display	analogue
maximum torque	650 Nm
Weight	3400 g
Socket for plug-in head	14×18 mm
Torque measuring accuracy	±3 %
Direction of tightening	For right and left-hand tightening
Exchangeable tool	Plug-in head
Scale graduation, 1 graduation =	2.5 Nm
Torque range	130 - 650 Nm
Torque range	100 - 480 lbfft
Standard	DIN EN ISO 6789
Reversible reading	Nm
Reversible reading	lbfft
Feedback	triggering
Adjustable trigger value	adjustable
Lever length including factory calibration reference dimension [I <sub>3</sub> ]	873 mm
Lever length without plug-in head [I <sub>1</sub> ]	848 mm
Adjusted reference dimension on the torque wrench [I <sub>2</sub> ]	25 mm
Trigger principle	mechanical short-travel release

Measurement process	Torque
Setting the trigger value	with adjustment scale
Connection format	for plug-in heads (rectangular socket)
Calibration	O1
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	akustisk
Release signalling	haptisk
Series	MANOSKOP® 730N
Type of product	Torque Wrench

## Services

Calibration Torque wrench maximum torque 1000 Nm	018820 1000
Labelling laser-etched Type	018940
DAkkS calibration Torque wrench maximum torque 1000 Nm	018830 1000

## Accessories

Plug-in ratchet reversible Type-Square drive 2-3/4 inch	657600 2-3/4
Plug-in ratchet reversible with QuickRelease ejector Type-Square drive 2-1/2 inch	657590 2-1/2
Plug-in ratchet reversible Type-Square drive 2-1/2 inch	657600 2-1/2
Plug-in ratchet reversible Type-Square drive 2-3/4HD inch	657600 2-3/4HD
Plug-in ratchet with ejector Type-Square drive 2-1/2 inch	657580 2-1/2
Plug-in ratchet reversible with ejector Type-Square drive 2-1/2 inch	657582 2-1/2