



## Torque wrench QuickSelect without plug-in head, maximum torque: 130 Nm



### Order data

Order number	657094 130
GTIN	4018754139538
Item class	63A

### Description

#### Version:

Sturdy compact one-armed torque wrench, adjustable to scale and self-triggering. The accuracy is sustained for many thousands of operations, because high quality material is used for all wearing parts with stressed parts loaded only briefly on each occasion. Body and handle are of sturdy square section. Scales adjustable. **Anti-clockwise tightening by pushing through the drive shank**

Without any plug-in head (basic model); see No. 657582 – 657950 for suitable plug-in heads.

**Units of measure:** N·m, lbf·ft.

#### Advantage:

- **Ergonomically shaped two-component handle, resistant to aggressive liquids such as fuel, Skydrol etc.**
- **The adjustment scale is placed behind a sight glass for protection against dirt and damage.**
- **Quick, precise, and reliable setting: Pull the setting knob, "Twist" to set the desired value and "Press" to save it. Setting knob moves easily since there is no spring pressure to be overcome.**

#### Function:

If the set value is reached while using the wrench, the wrench triggers giving a "signal" (acoustic and perceptible) and is then immediately ready for use again.

#### Application:

Since the set torque can be varied, it is ideal for repairs and short series production.

#### Standard:

Geprüft nach DIN EN ISO 6789.

#### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy:  $\pm 3\%$   
 Exchangeable tool: Plug-in head  
 Test certificate: Manufacturer's test certificate  
 Calibration: O1  
 Overall length L: 421 mm  
 Torque range: 25 - 130 Nm  
 Torque range: 20 - 95 lbfft  
 Scale graduation, 1 graduation =: 0.5 Nm  
 Weight: 1128 g  
 Adjusted reference dimension on the torque wrench [I<sub>2</sub>]: 25 mm

## Technical description

Display	analogue
maximum torque	130 Nm
Weight	1128 g
Socket for plug-in head	14×18 mm
Torque measuring accuracy	$\pm 3\%$
Direction of tightening	For right and left-hand tightening
Exchangeable tool	Plug-in head
Scale graduation, 1 graduation =	0.5 Nm
Torque range	25 - 130 Nm
Torque range	20 - 95 lbfft
Lever length including factory calibration reference dimension [I <sub>3</sub> ]	404 mm
Setting the trigger value	with adjustment scale
Adjusted reference dimension on the torque wrench [I <sub>2</sub> ]	25 mm
Standard	DIN EN ISO 6789
Lever length without plug-in head [I <sub>1</sub> ]	379 mm
Reversible reading	Nm
Reversible reading	lbfft
Connection format	for plug-in heads (rectangular socket)
Trigger principle	mechanical short-travel release
Adjustable trigger value	adjustable

Overall length L	421 mm
Feedback	triggering
Measurement process	Torque
Calibration	O1
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	akustisk
Release signalling	haptisk
Series	MANOSKOP® 730N
Type of product	Torque Wrench

## Services

Calibration Torque wrench maximum torque 400 Nm	018820 400
Labelling laser-etched Type	018940
DAkkS calibration Torque wrench maximum torque 1000 Nm	018830 1000

## Accessories

Plug-in ratchet Square drive 2-3/4 inch	657620 2-3/4
Plug-in ratchet reversible with QuickRelease ejector Type-Square drive 2-1/2 inch	657590 2-1/2
Plug-in ratchet with ejector Type-Square drive 2-1/2 inch	657580 2-1/2
Square drive plug-in head Type-Square drive 2-3/4 inch	657700 2-3/4
Plug-in ratchet reversible Type-Square drive 2-1/2 inch	657600 2-1/2
Plug-in ratchet reversible Type-Square drive 2-3/4HD inch	657600 2-3/4HD
Square drive plug-in head Type-Square drive 2-1/2 inch	657700 2-1/2
Plug-in ratchet reversible Type-Square drive 2-3/4 inch	657600 2-3/4
Plug-in ratchet Square drive 2-1/2 inch	657620 2-1/2
Plug-in ratchet Type-Square drive 2-1/2 inch	657630 2-1/2

Plug-in ratchet reversible with ejector Type-Square drive  
2-1/2 inch

657582 2-1/2

Plug-in ratchet Type-Square drive 2-3/4 inch

657630 2-3/4