



## Torque wrench with square plug-in head, Maximum torque: 400 Nm



### Order data

Order number	657205 400
GTIN	2050002047310
Item class	63A

### Description

#### Version:

Sturdy compact one-armed torque wrench, adjustable to scale and self-triggering. The accuracy is sustained for many thousands of operations, because high quality material is used for all wearing parts with stressed parts loaded only briefly on each occasion. Body and handle are of sturdy square section. Scales adjustable. **Anti-clockwise tightening by pushing through the drive shank**

With **square drive plug-in head**. **Units of measure:** N·m, lbf·ft.

#### Function:

**Adjustment:** Quick adjustment of the torque with the slide setting button. The value is fixed using the locking key in the handle.

Quick adjustment of the torque with the slide setting button. The value is fixed using the locking key in the handle.

#### Application:

Since the set torque can be varied, it is ideal for repairs and short series production.

#### Standard:

Geprüft nach DIN EN ISO 6789.

#### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy:  $\pm 4\%$

Exchangeable tool: Plug-in head

Test certificate: Manufacturer's test certificate

Calibration: O1

Torque range: 80 - 400 Nm

Torque range: 60 - 300 lbf·ft

Scale graduation, 1 graduation =: 10 Nm

Weight: 1660 g

Adjusted reference dimension on the torque wrench [ $l_2$ ]: 25 mm

Square drive: 3/4 inch

## Technical description

Weight	1660 g
Scale graduation, 1 graduation =	10 Nm
Direction of tightening	For right and left-hand tightening
Display	analogue
Socket for plug-in head	14×18 mm
Exchangeable tool	Plug-in head
Torque measuring accuracy	±4 %
Square drive	3/4 inch
maximum torque	400 Nm
Torque range	80 - 400 Nm
Torque range	60 - 300 lbfft
Adjusted reference dimension on the torque wrench [l <sub>2</sub> ]	25 mm
Standard	DIN EN ISO 6789
Connection format	for plug-in heads (rectangular socket)
Setting the trigger value	with adjustment scale
Adjustable trigger value	adjustable
Trigger principle	mechanical short-travel release
Reversible reading	Nm
Measurement process	Torque
Lever length without plug-in head [l <sub>1</sub> ]	570 mm
Lever length including factory calibration reference dimension [l <sub>3</sub> ]	595 mm
Feedback	triggering
Calibration	O1
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	akustisk

Release signalling	haptisk
Measurement technology	mechanical
Series	MANOSKOP® 730 Quick
Deflection function	no
Slipper function	no
Quick release/ quick-change function	no
Memory pointer	no
Type of product	Torque Wrench

### Services

Labelling laser-etched Type	018940
Calibration Torque wrench maximum torque 400 Nm	018820 400
DAkKS calibration Torque wrench maximum torque 1000 Nm	018830 1000

### Accessories

Plug-in ratchet reversible with QuickRelease ejector Type-Square drive 2-1/2 inch	657590 2-1/2
Plug-in ratchet Square drive 2-3/4 inch	657620 2-3/4
Square drive plug-in head Type-Square drive 2-1/2 inch	657700 2-1/2
Plug-in ratchet with ejector Type-Square drive 2-1/2 inch	657580 2-1/2
Plug-in ratchet reversible Type-Square drive 2-3/4 inch	657600 2-3/4
Plug-in ratchet Square drive 2-1/2 inch	657620 2-1/2
Plug-in ratchet reversible Type-Square drive 2-3/4HD inch	657600 2-3/4HD
Square drive plug-in head Type-Square drive 2-3/4 inch	657700 2-3/4
Plug-in ratchet reversible Type-Square drive 2-1/2 inch	657600 2-1/2
Spare handle for torque wrenches Type 3	657211 3
Spare handle for torque wrenches Type 4	657211 4
Scale window with magnifying glass for torque wrench Type 2	657212 2

Green slide for torque wrench Type 2	657213 2
Plug-in ratchet Type-Square drive 2-1/2 inch	657630 2-1/2
Plug-in ratchet Type-Square drive 2-3/4 inch	657630 2-3/4
Plug-in ratchet reversible with ejector Type-Square drive 2-1/2 inch	657582 2-1/2