



Torque wrench with setting scale, maximum torque: 10 Nm



Order data

Order number	657235 10
GTIN	4571141275528
Item class	66F

Description

Version:

Units of measure: N·m.

Torque wrench, adjustable using micrometer scale, with protection against accidental changes to the setting. With reversible ratchet head and square drive for sockets. With knurled metal handle.

Function:

On reaching the set torque value the wrench triggers giving a "signal" (acoustic and perceptible) and is then immediately ready for use again.

Application:

For medium and large batch productions.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy: $\pm 3\%$

Test certificate: Manufacturer's test certificate

Calibration: O1

Overall length L: 195 mm

Torque range: 2 - 10 Nm

Scale graduation, 1 graduation =: 0.1 Nm

Weight: 190 g

Square drive: 1/4 inch

Technical description

maximum torque	10 Nm
Square drive	1/4 inch
Display	analogue
Weight	190 g
Torque measuring accuracy	±3 %
Direction of tightening	Right-hand tightening
Scale graduation, 1 graduation =	0.1 Nm
Torque range	2 - 10 Nm
Lever length including factory calibration reference dimension [l ₃]	135 mm
Overall length L	195 mm
Adjustable trigger value	adjustable
Standard	DIN EN ISO 6789
Setting the trigger value	with adjustment scale
Reversible reading	Nm
Feedback	triggering
Connection format	Push-through square drive (ratchet)
Trigger principle	mechanical short-travel release
Measurement process	Torque
Calibration	O1
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	akustisk
Release signalling	haptisk
Measurement technology	mechanical
Type of product	Torque Wrench

Services

Labelling laser-etched Type	018940
Calibration Torque wrench maximum torque 400 Nm	018820 400

