



Torque wrench with setting scale, maximum torque: 1400 Nm



Order data

Order number	657235 1400
GTIN	4571141276440
Item class	66F

Description

Version:

Units of measure: N·m.

Torque wrench, adjustable using micrometer scale, with protection against accidental changes to the setting. With reversible ratchet head and square drive for sockets. With knurled metal handle.

Function:

On reaching the set torque value the wrench triggers giving a "signal" (acoustic and perceptible) and is then immediately ready for use again.

Application:

For medium and large batch productions.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789. Use only sockets with lock hole.

Direction of tightening: Right-hand tightening

Torque measuring accuracy: $\pm 3\%$

Test certificate: Manufacturer's test certificate

Calibration: O1

Overall length L: 1787 mm

Torque range: 300 - 1400 Nm

Scale graduation, 1 graduation =: 10 Nm

Weight: 10800 g

Square drive: 1 inch

Technical description

Display	analogue
---------	----------

Weight	10800 g
Square drive	1 inch
maximum torque	1400 Nm
Torque measuring accuracy	±3 %
Direction of tightening	Right-hand tightening
Scale graduation, 1 graduation =	10 Nm
Torque range	300 - 1400 Nm
Setting the trigger value	with adjustment scale
Overall length L	1787 mm
Trigger principle	mechanical short-travel release
Standard	DIN EN ISO 6789
Adjustable trigger value	adjustable
Lever length including factory calibration reference dimension [L ₃]	1650 mm
Feedback	triggering
Connection format	Push-through square drive (ratchet)
Measurement process	Torque
Reversible reading	Nm
Calibration	O1
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	akustisk
Release signalling	haptisk
Measurement technology	mechanical
Type of product	Torque Wrench

Services

Calibration Torque wrench maximum torque 2000 Nm	018820 2000
Labelling laser-etched Type	018940

