



Torque wrench with setting scale, maximum torque: 2800 Nm



Order data

Order number	657235 2800
GTIN	4571141276464
Item class	66F

Description

Version:

Units of measure: N·m.

Torque wrench, adjustable using micrometer scale, with protection against accidental changes to the setting. With reversible ratchet head and square drive for sockets. With knurled metal handle.

Function:

On reaching the set torque value the wrench triggers giving a "signal" (acoustic and perceptible) and is then immediately ready for use again.

Application:

For medium and large batch productions.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789. Use only sockets with lock hole.

Direction of tightening: Right-hand tightening

Torque measuring accuracy: $\pm 3\%$

Test certificate: Manufacturer's test certificate

Calibration: O1

Overall length L: 2405 mm

Torque range: 800 - 2800 Nm

Scale graduation, 1 graduation =: 20 Nm

Weight: 24500 g

Square drive: 1.1/2 inch

Technical description

maximum torque	2800 Nm
----------------	---------

Square drive	1.1/2 inch
Weight	24500 g
Display	analogue
Torque measuring accuracy	±3 %
Direction of tightening	Right-hand tightening
Scale graduation, 1 graduation =	20 Nm
Torque range	800 - 2800 Nm
Lever length including factory calibration reference dimension [l ₃]	2240 mm
Reversible reading	Nm
Setting the trigger value	with adjustment scale
Overall length L	2405 mm
Measurement process	Torque
Standard	DIN EN ISO 6789
Adjustable trigger value	adjustable
Feedback	triggering
Trigger principle	mechanical short-travel release
Connection format	Push-through square drive (ratchet)
Calibration	O1
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	akustisk
Release signalling	haptisk
Type of product	Torque Wrench

Services

Labelling laser-etched Type	018940
-----------------------------	--------

