# Your Torque Partner

### Torque wrench with setting scale, maximum torque: 420 Nm



### Order data

Order number	657235 420
GTIN	4560138447604
Item class	66F

### Description

#### Version:

#### Units of measure: N·m.

Torque wrench, adjustable using micrometer scale, with protection against accidental changes to the setting. With reversible ratchet head and square drive for sockets. With knurled metal handle.

#### **Function:**

On reaching the set torque value the wrench triggers giving a "signal" (acoustic and perceptible) and is then immediately ready for use again.

#### Application:

For medium and large batch productions.

#### Standard:

Geprüft nach DIN EN ISO 6789.

#### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy: ±3 %

Test certificate: Manufacturer's test certificate

Calibration: O1

Overall length L: 995 mm

Torque range: 60 - 420 Nm

Scale graduation, 1 graduation =: 3 Nm

Weight: 4000 g

Square drive: 3/4 inch

### **Technical description**

#### Weight

4000 g

© Hoffmann GmbH Qualitätswerkzeuge

Display	analogue
maximum torque	420 Nm
Square drive	3/4 inch
Torque measuring accuracy	±3 %
Direction of tightening	Right-hand tightening
Scale graduation, 1 graduation =	3 Nm
Torque range	60 - 420 Nm
Lever length including factory calibration reference dimension $[I_3]$	900 mm
Overall length L	995 mm
Adjustable trigger value	adjustable
Measurement process	Torque
Feedback	triggering
Connection format	Push-through square drive (ratchet)
Standard	DIN EN ISO 6789
Setting the trigger value	with adjustment scale
Trigger principle	mechanical short-travel release
Reversible reading	Nm
Calibration	01
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	akustisk
Release signalling	haptisk
Type of product	Torque Wrench

## Services

Labelling laser-etched Type	018940
Calibration Torque wrench maximum torque 1000 Nm	018820 1000
	018830 1000

DAkkS calibration Torque wrench maximum torque 1000 Nm