



Torque wrench with setting scale, maximum torque: 5 Nm



Order data

Order number	657235 5
GTIN	4571141275498
Item class	66F

Description

Version:

Units of measure: N·m.

Torque wrench, adjustable using micrometer scale, with protection against accidental changes to the setting. With reversible ratchet head and square drive for sockets. With knurled metal handle.

Function:

On reaching the set torque value the wrench triggers giving a "signal" (acoustic and perceptible) and is then immediately ready for use again.

Application:

For medium and large batch productions.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy: $\pm 3\%$

Test certificate: Manufacturer's test certificate

Calibration: O1

Overall length L: 194 mm

Torque range: 1 - 5 Nm

Scale graduation, 1 graduation =: 0.05 Nm

Weight: 160 g

Square drive: 1/4 inch

Technical description

Weight	160 g
Display	analogue
Square drive	1/4 inch
maximum torque	5 Nm
Torque measuring accuracy	±3 %
Direction of tightening	Right-hand tightening
Scale graduation, 1 graduation =	0.05 Nm
Torque range	1 - 5 Nm
Overall length L	194 mm
Lever length including factory calibration reference dimension [L ₃]	121 mm
Setting the trigger value	with adjustment scale
Reversible reading	Nm
Measurement process	Torque
Connection format	Push-through square drive (ratchet)
Feedback	triggering
Adjustable trigger value	adjustable
Trigger principle	mechanical short-travel release
Standard	DIN EN ISO 6789
Calibration	O1
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	akustisk
Release signalling	haptisk
Measurement technology	mechanical
Type of product	Torque Wrench

Services

Labelling laser-etched Type	018940
Calibration Torque wrench maximum torque 400 Nm	018820 400

