



## Torque wrench with setting scale, maximum torque: 50 Nm



### Order data

Order number	657235 50
GTIN	4560138448076
Item class	66F

### Description

**Version:**

**Units of measure:** N·m.

Torque wrench, adjustable using micrometer scale, with protection against accidental changes to the setting. With reversible ratchet head and square drive for sockets. With synthetic resin handle.

**Function:**

On reaching the set torque value the wrench triggers giving a "signal" (acoustic and perceptible) and is then immediately ready for use again.

**Application:**

For medium and large batch productions.

**Standard:**

Geprüft nach DIN EN ISO 6789.

**Note:**

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy:  $\pm 3\%$

Test certificate: Manufacturer's test certificate

Calibration: O1

Overall length L: 260 mm

Torque range: 10 - 50 Nm

Scale graduation, 1 graduation =: 0.5 Nm

Weight: 400 g

Square drive: 3/8 inch

### Technical description

Weight	400 g
--------	-------

Display	analogue
Square drive	3/8 inch
maximum torque	50 Nm
Torque measuring accuracy	±3 %
Direction of tightening	Right-hand tightening
Scale graduation, 1 graduation =	0.5 Nm
Torque range	10 - 50 Nm
Reversible reading	Nm
Measurement process	Torque
Adjustable trigger value	adjustable
Standard	DIN EN ISO 6789
Lever length including factory calibration reference dimension [l <sub>3</sub> ]	180 mm
Trigger principle	mechanical short-travel release
Setting the trigger value	with adjustment scale
Feedback	triggering
Connection format	Push-through square drive (ratchet)
Overall length L	260 mm
Calibration	O1
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	akustisk
Release signalling	haptisk
Measurement technology	mechanical
Type of product	Torque Wrench

## Services

Labelling laser-etched Type	018940
Calibration Torque wrench maximum torque 400 Nm	018820 400
	018830 1000

DAkKS calibration Torque wrench maximum torque 1000  
Nm

---