HOLEX

Torque Wrench with ratchet, maximum torque: 20 Nm



Order data

Order number	657272 20
GTIN	4045197439420
Item class	62E

Description

Version:

Robust torque wrench, adjustable with micrometer scale, with protection against accidental changes to the setting.

Integral ratchet to accept sockets.

Units of measure: N·m, lbf·ft. With **reversible ratchet** and fixed square drive pin – **only for right-hand tightening.**

Function:

On reaching the set torque value the wrench triggers giving a "signal" (audible and perceptible) and is then immediately ready for use again.

Application:

For small to medium series.

Standard:

Geprüft nach DIN EN ISO 6789.

Accuracy:

 ± 3 % of the displayed value.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy: ±3 %

Test certificate: Manufacturer's test certificate

Calibration: O1

Overall length L: 232 mm

Torque range: 4 - 20 Nm

Scale graduation, 1 graduation =: 0.1 Nm

Weight: 400 g

Square drive: 1/4 inch

Technical description

maximum torque	20 Nm
Direction of tightening	Right-hand tightening
Display	analogue
Weight	400 g
Square drive	1/4 inch
Scale graduation, 1 graduation =	0.1 Nm
Torque measuring accuracy	±3 %
Torque range	4 - 20 Nm
Feedback	triggering
Setting the trigger value	with adjustment scale
Reversible reading	Nm
Reversible reading	lbfft
Standard	DIN EN ISO 6789
Measurement process	Torque
Adjustable trigger value	adjustable
Overall length L	232 mm
Lever length including factory calibration reference dimension $[I_3]$	166 mm
Connection format	Push-through square drive (ratchet)
Trigger principle	mechanical short-travel release
Calibration	01
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	acoustic
Release signalling	haptisk
Measurement technology	mechanical
Type of product	Torque Wrench

Services

© Hoffmann GmbH Qualitätswerkzeuge

Calibration Torque wrench maximum torque 400 Nm	018820 400
Labelling laser-etched Type	018940
Accessories	