

## Torque wrench base unit without plug-in head, maximum torque: 200 Nm



## **Order data**

Order number	657277 200
GTIN	4045197804167
Item class	62E

## **Description**

#### **Version:**

Robust torque wrench, adjustable with micrometer scale, with protection against accidental changes to the setting.

Basic tool with square plug-in socket (without plug-in head). Suitable spare jaws No. 657582 - 657950.

Units of measure: N·m, lbf·ft.

### **Function:**

On reaching the set torque value the wrench triggers giving a "signal" (audible and perceptible) and is then immediately ready for use again.

#### **Application:**

For small to medium series.

#### Standard:

Geprüft nach DIN EN ISO 6789.

## **Accuracy:**

±3 % of the displayed value.

#### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy: ±3 % Exchangeable tool: Plug-in head

Test certificate: Manufacturer's test certificate

Calibration: O1

Overall length L: 465 mm Torque range: 40 - 200 Nm

Scale graduation, 1 graduation =: 1 Nm

Weight: 1000 g

Adjusted reference dimension on the torque wrench [l<sub>2</sub>]: 40 mm

Socket for plug-in head: 14×18 mm

# **Technical description**

Scale graduation, 1 graduation =	1 Nm
maximum torque	200 Nm
Exchangeable tool	Plug-in head
Weight	1000 g
Direction of tightening	For right and left-hand tightening
Socket for plug-in head	14×18 mm
Torque measuring accuracy	±3 %
Display	analogue
Torque range	40 - 200 Nm
Trigger principle	mechanical short-travel release
Measurement process	Torque
Lever length including factory calibration reference dimension [I <sub>3</sub> ]	369 mm
Setting the trigger value	with adjustment scale
Adjusted reference dimension on the torque wrench [l <sub>2</sub> ]	40 mm
Lever length without plug-in head [l <sub>1</sub> ]	329 mm
Connection format	for plug-in heads (rectangular socket)
Standard	DIN EN ISO 6789
Feedback	triggering
Reversible reading	Nm
Reversible reading	lbfft
Adjustable trigger value	adjustable
Overall length L	465 mm
Calibration	01
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical



Release signalling	acoustic
Release signalling	haptisk
Type of product	Torque Wrench
Services	

Labelling laser-etched Type	018940
Calibration Torque wrench maximum torque 400 Nm	018820 400
DAkkS calibration Torque wrench maximum torque 1000 Nm	018830 1000

## **Accessories**

Plug-in ratchet Square drive 2-3/4 inch	657620 2-3/4
Plug-in ratchet Square drive 2-1/2 inch	657620 2-1/2
Plug-in ratchet with ejector Type-Square drive 2-1/2 inch	657580 2-1/2
Plug-in ratchet Type-Square drive 2-1/2 inch	657630 2-1/2
Plug-in ratchet Type-Square drive 2-3/4 inch	657630 2-3/4
Plug-in ratchet reversible with ejector Type-Square drive 2-1/2 inch	657582 2-1/2