



Torque wrench base unit, maximum torque: 200 Nm



Order data

| | |
|--------------|---------------|
| Order number | 657500 200 |
| GTIN | 4045197566461 |
| Item class | 62E |

Description

Version:

Single-handed torque wrench without a setting scale. Wrench setting using torque analyser.

Left-hand tightening by reversing the plug-in head.

Without plug-in head (base model); see No. 657582 – 657590 for suitable plug-in heads.

Function:

On reaching the set torque value the wrench triggers giving a "signal" (audible and perceptible) and is then immediately ready for use again.

Application:

For controlled screw tightening etc. to specified torques in batch productions.

Standard:

Geprüft nach DIN EN ISO 6789.

Optional extras:

Adjustment wrench No. 657520.

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy: $\pm 4\%$

Exchangeable tool: Plug-in head

Calibration: O6

Calibration: O7

Overall length L: 405 mm

Torque range: 50 - 200 Nm

Weight: 720 g

Socket for plug-in head: 14x18 mm

Technical description

| | |
|----------------|--------|
| Weight | 720 g |
| maximum torque | 200 Nm |

| | |
|---------------------------|---|
| Socket for plug-in head | 14×18 mm |
| Torque measuring accuracy | ±4 % |
| Direction of tightening | For right and left-hand tightening |
| Exchangeable tool | Plug-in head |
| Torque range | 50 - 200 Nm |
| Overall length L | 405 mm |
| Measurement process | Torque |
| Reversible reading | Nm |
| Trigger principle | mechanical short-travel release |
| Standard | DIN EN ISO 6789 |
| Feedback | triggering |
| Connection format | for plug-in heads (rectangular socket) |
| Adjustable trigger value | pre-set |
| Setting the trigger value | uden indstillingskala (kræver testapparat) |
| Calibration | O6 |
| Calibration | O7 |
| Data can be recorded | no |
| Release signalling | akustisk |
| Release signalling | haptisk |
| Measurement technology | mechanical |
| Type of product | Torque Wrench |

Services

| | |
|---|------------|
| Calibration Torque wrench maximum torque 400 Nm | 018820 400 |
| Adjustment Torque wrench without scale | 018890 |

Accessories

| | |
|---|------------|
| Torque analyser for torque wrenches "SmartCheck" maximum torque 100 Nm | 654650 100 |
|---|------------|

| | |
|--|--------------|
| Electronic torque analyser "ProTest" maximum torque 400 Nm | 654460 400 |
| Setting wrench for the torque value | 657520 |
| Plug-in ratchet with ejector Type-Square drive 2-1/2 inch | 657580 2-1/2 |
| Plug-in ratchet Square drive 2-1/2 inch | 657620 2-1/2 |
| Torque analyser for torque wrenches "SmartCheck" maximum torque 400 Nm | 654650 400 |
| Plug-in ratchet Square drive 2-3/4 inch | 657620 2-3/4 |
| Plug-in ratchet reversible with ejector Type-Square drive 2-1/2 inch | 657582 2-1/2 |
| Plug-in ratchet Type-Square drive 2-1/2 inch | 657630 2-1/2 |
| Plug-in ratchet Type-Square drive 2-3/4 inch | 657630 2-3/4 |