



Torque wrench, fully insulated with push-through square, Maximum torque: 10 Nm



Order data

Order number	657556 10
GTIN	4000896200023
Item class	630

Description

Version:

Torque wrench **fully insulated up to 1000 V to DIN EN 60900 / VDE 0682-201.**

Single-handed torque wrench, adjustable using the scale, with protection against accidental changes to the setting. Integral ratchet, **reversible left-hand and right-hand** tightening by push-through drive square.

Units of measure: N·m.

Advantage:

Long working life and accuracy due to availability of calibration, adjustment and repair.

Function:

On reaching the set torque value the wrench triggers giving a "signal" (audible and perceptible) and is then immediately ready for use again.

Standard:

Geprüft nach DIN EN ISO 6789.

Accuracy:

±6% of the set value.

Attention:

Any repairs must be performed on in the HAZET Service Centre, since the wrench must be subjected after repair to an individual 10,000 V test to DIN EN 60900 / VDE 0682-201!

Note:

For working at voltages up to 1000 Volts. In safety areas only **fully insulated** tools may be used in combination.

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

electrical insulation: VDE 1000 V

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy: ±6 %

Test certificate: Manufacturer's test certificate
 Calibration: O1
 Overall length L: 275 mm
 Torque range: 2 - 10 Nm
 Scale graduation, 1 graduation =: 0.2 Nm
 Weight: 590 g
 Square drive: 3/8 inch

Technical description

Direction of tightening	For right and left-hand tightening
Square drive	3/8 inch
Display	analogue
Weight	590 g
maximum torque	10 Nm
Torque measuring accuracy	±6 %
Scale graduation, 1 graduation =	0.2 Nm
Torque range	2 - 10 Nm
Reversible reading	Nm
Setting the trigger value	with adjustment scale
Adjustable trigger value	adjustable
Overall length L	275 mm
Standard	DIN EN ISO 6789
Measurement process	Torque
Lever length including factory calibration reference dimension [L ₃]	208 mm
Feedback	triggering
Connection format	Push-through square drive (ratchet)
Trigger principle	mechanical short-travel release
Calibration	O1
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical

Release signalling	akustisk
Release signalling	haptisk
electrical insulation	VDE 1000 V
Deflection function	no
Slipper function	no
Quick release/ quick-change function	no
Memory pointer	no
Type of product	Torque Wrench

Services

Calibration Torque wrench maximum torque 400 Nm	018820 400
---	------------