



Torque wrench, fully insulated with push-through square, Maximum torque: 120 Nm



Order data

Order number	657556 120
GTIN	4000896229024
Item class	630

Description

Version:

Torque wrench **fully insulated up to 1000 V to DIN EN 60900 / VDE 0682-201.**

Single-handed torque wrench, adjustable using the scale, with protection against accidental changes to the setting. Integral ratchet, **reversible left-hand and right-hand** tightening by push-through drive square.

Units of measure: N·m.

Advantage:

Long working life and accuracy due to availability of calibration, adjustment and repair.

Function:

On reaching the set torque value the wrench triggers giving a "signal" (audible and perceptible) and is then immediately ready for use again.

Standard:

Geprüft nach DIN EN ISO 6789.

Accuracy:

±4% of the set value.

Attention:

Any repairs must be performed on in the HAZET Service Centre, since the wrench must be subjected after repair to an individual 10,000 V test to DIN EN 60900 / VDE 0682-201!

Note:

For working at voltages up to 1000 Volts. In safety areas only **fully insulated** tools may be used in combination.

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

electrical insulation: VDE 1000 V

Direction of tightening: For right and left-hand tightening

Torque measuring accuracy: ±4 %

Test certificate: Manufacturer's test certificate
 Calibration: O1
 Overall length L: 420 mm
 Torque range: 20 - 120 Nm
 Scale graduation, 1 graduation =: 1 Nm
 Weight: 1440 g
 Square drive: 1/2 inch

Technical description

Overall length L	420 mm
Standard	DIN EN ISO 6789
Setting the trigger value	with adjustment scale
Display	analogue
Data can be recorded	no
Feedback	triggering
Measurement process	Torque
Scale graduation, 1 graduation =	1 Nm
Trigger principle	mechanical short-travel release
Weight	1440 g
Release signalling	acoustic
Release signalling	haptisk
Torque measuring accuracy	±4 %
Connection format	Push-through square drive (ratchet)
Measurement technology	mechanical
Direction of tightening	For right and left-hand tightening
Calibration	O1
Adjustable trigger value	adjustable
Square drive	1/2 inch
Lever length including factory calibration reference dimension [I ₃]	345 mm
Reversible reading	lbfft
Test certificate	Manufacturer's test certificate

maximum torque	120 Nm
Torque range	20 - 120 Nm
electrical insulation	VDE 1000 V
Deflection function	no
Slipper function	no
Quick release/ quick-change function	no
Memory pointer	no
Type of product	Torque Wrench