Garant

Torque wrench "Slipper" with scale, maximum torque: 10 Nm



Order data

Order number	657762 10
GTIN	4045197891624
Item class	61E

Description

Version:

The special slipping trigger mechanism **reliably prevents unintentional overtightening.** Torque wrench with **micrometer scale for setting**, self-triggering. Hold in position at the end of the handle against inadvertent adjustment. With integral ratchet.

Units of measure: N·m.

Units of measure

Advantage:

Precision triggering mechanism facilitates working in inaccessible places.

Function:

On reaching the set torque value the wrench triggers a clearly detectable deflection and is then immediately ready for use again. The special trigger mechanism ensures that the set torque values are reliably achieved, **but not exceeded**.

Application:

For medium to larger batch productions.

Standard:

Geprüft nach DIN EN ISO 6789.

Accuracy:

±6 % of the set value. Direction of tightening: For right-hand tightening Torque measuring accuracy: ±6 % Test certificate: Manufacturer's test certificate Calibration: O1 Overall length L: 204 mm Torque range: 2 - 10 Nm Scale graduation, 1 graduation =: 0.1 Nm Weight: 235 g Square drive: 1/4 inch

Technical description

DisplayanalogueSquare drive1/4 inchScale graduation, 1 graduation =0.1 NmDirection of tighteningFor right-hand tighteningmaximum torque10 NmWeight235 gTorque measuring accuracy±6 %StandardDIN EN ISO 6789Setting the trigger valuewith adjustment scaleOverall length L204 mmConnection formatPush-through square drive (ratchet)Lever length including factory calibration reference dimension [l,]140 mmReversible readingTorqueAdjustable trigger valueadjustableLever length without plug-in head [l,]135 mmFeedbackTriggeringCalibrationO1Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingAdjustskeRelease signallingStalkiskRelease signallingStalkiskSeriesSlipper	Torque range	2 - 10 Nm
Scale graduation, 1 graduation =0.1 NmDirection of tighteningFor right-hand tighteningmaximum torque10 NmWeight235 gTorque measuring accuracy±6 %StandardDIN EN ISO 6789Setting the trigger valuewith adjustment scaleOverall length L204 mmConnection formatPush-through square drive (ratchet)Lever length including factory calibration reference dimension [I,]140 mmReversible readingNmTrigger principleMechanical slip clutchMeasurement processTorqueAdjustable trigger valueadjustableLever length without plug-in head [I,]135 mmFeedbackTriggeringCalibrationO1Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingAikustiskRelease signallingAikustisk	Display	analogue
Direction of tighteningFor right-hand tighteningmaximum torque10 NmWeight235 gTorque measuring accuracy±6 %StandardDIN EN ISO 6789Setting the trigger valuewith adjustment scaleOverall length L204 mmConnection formatPush-through square drive (ratchet)Lever length including factory calibration reference dimension [l,]140 mmReversible readingNmTrigger principlemechanical slip clutchMeasurement processTorqueAdjustable trigger valueadjustableLever length without plug-in head [l,]135 mmFeedbackO1CalibrationO1Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingoptiskRelease signallingakustiskRelease signallinghaptisk	Square drive	1/4 inch
maximum torque10 NmWeight235 gTorque measuring accuracy±6 %StandardDIN EN ISO 6789Setting the trigger valuewith adjustment scaleOverall length L204 mmConnection formatPush-through square drive (ratchet)Lever length including factory calibration reference dimension [l,]140 mmReversible readingMmTrigger principleMechanical slip clutchMeasurement processTorqueAdjustable trigger valueadjustableLever length without plug-in head [l,]135 mmFeedbackTriggeringCalibrationO1Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingakustiskRelease signallingakustiskRelease signallinghaptisk	Scale graduation, 1 graduation =	0.1 Nm
Weight235 gVeight235 gTorque measuring accuracy±6 %StandardDIN EN ISO 6789Setting the trigger valuewith adjustment scaleOverall length L204 mmConnection formatPush-through square drive (ratchet)Lever length including factory calibration reference dimension [l ₃]140 mmReversible readingMmTrigger principleMechanical slip clutchMeasurement processTorqueAdjustable trigger valueadjustableLever length without plug-in head [l ₁]135 mmFeedbackTriggeringCalibrationO1Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingakustiskRelease signallingakustisk	Direction of tightening	For right-hand tightening
Torque measuring accuracy±6 %StandardDIN EN ISO 6789Setting the trigger valuewith adjustment scaleOverall length L204 mmConnection formatPush-through square drive (ratchet)Lever length including factory calibration reference dimension [1 ₃]140 mmReversible readingMmTrigger principlemechanical slip clutchMeasurement processTorqueAdjustable trigger valueadjustableLever length without plug-in head [1,]135 mmFeedbackO1Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingoptiskRelease signallingakustiskRelease signallinghaptisk	maximum torque	10 Nm
It is a structureDIN EN ISO 6789Setting the trigger valuewith adjustment scaleOverall length L204 mmConnection formatPush-through square drive (ratchet)Lever length including factory calibration reference dimension [l,]140 mmReversible readingMmTrigger principleMechanical slip clutchMeasurement processTorqueAdjustable trigger valueadjustableLever length without plug-in head [l,]135 mmFeedbackCollCalibration01Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingoptiskRelease signallingakustiskRelease signallinghaptisk	Weight	235 g
Setting the trigger valuewith adjustment scaleOverall length L204 mmConnection formatPush-through square drive (ratchet)Lever length including factory calibration reference dimension [l _s]140 mmReversible readingMmTrigger principleMechanical slip clutchMeasurement processTorqueAdjustable trigger valueadjustableLever length without plug-in head [l ₁]135 mmFeedbackO1CalibrationO1Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingAkustiskRelease signallingAkustisk	Torque measuring accuracy	±6 %
Overall length L204 mmConnection formatPush-through square drive (ratchet)Lever length including factory calibration reference dimension [I,]140 mmReversible readingNmTrigger principlemechanical slip clutchMeasurement processTorqueAdjustable trigger valueadjustableLever length without plug-in head [I,]135 mmFeedbacktriggeringCalibrationO1Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingakustiskRelease signallinghaptisk	Standard	DIN EN ISO 6789
Connection formatPush-through square drive (ratchet)Lever length including factory calibration reference dimension [l ₃]140 mmReversible readingNmTrigger principlemechanical slip clutchMeasurement processTorqueAdjustable trigger valueadjustableLever length without plug-in head [l ₁]135 mmFeedbackO1CalibrationO1Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingakustiskRelease signallinghaptisk	Setting the trigger value	with adjustment scale
Lever length including factory calibration reference dimension [l_3]140 mmReversible readingNmTrigger principlemechanical slip clutchMeasurement processTorqueAdjustable trigger valueadjustableLever length without plug-in head [l_1]135 mmFeedbackC1CalibrationO1Test certificateManufacturer's test certificateData can be recordedmechanicalRelease signallingoptiskRelease signallingakustiskRelease signallinghaptisk	Overall length L	204 mm
dimension [I,]140 mmReversible readingNmTrigger principlemechanical slip clutchMeasurement processTorqueAdjustable trigger valueadjustableLever length without plug-in head [I,]135 mmFeedbacktriggeringCalibrationO1Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingoptiskRelease signallinghaptisk	Connection format	Push-through square drive (ratchet)
Trigger principlemechanical slip clutchMeasurement processTorqueAdjustable trigger valueadjustableLever length without plug-in head [l ₁]135 mmFeedbacktriggeringCalibrationO1Test certificateManufacturer's test certificateData can be recordedmechanicalMeasurement technologymechanicalRelease signallingakustiskRelease signallinghaptisk		140 mm
Measurement processTorqueAdjustable trigger valueadjustableLever length without plug-in head [l ₁]135 mmFeedbacktriggeringCalibrationO1Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingoptiskRelease signallingakustiskRelease signallinghaptisk	Reversible reading	Nm
Adjustable trigger valueadjustableLever length without plug-in head [l_1]135 mmFeedbacktriggeringCalibrationO1Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingoptiskRelease signallinghaptisk	Trigger principle	mechanical slip clutch
Lever length without plug-in head [l,]135 mmFeedbacktriggeringCalibrationO1Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingoptiskRelease signallingakustiskRelease signallinghaptisk	Measurement process	Torque
FeedbacktriggeringCalibrationO1Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingoptiskRelease signallingakustiskRelease signallinghaptisk	Adjustable trigger value	
CalibrationO1Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingoptiskRelease signallingakustiskRelease signallinghaptisk	Rajustable rigger value	adjustable
Test certificateManufacturer's test certificateData can be recordednoMeasurement technologymechanicalRelease signallingoptiskRelease signallingakustiskRelease signallinghaptisk		
Data can be recordednoMeasurement technologymechanicalRelease signallingoptiskRelease signallingakustiskRelease signallinghaptisk	Lever length without plug-in head [l ₁]	135 mm
Measurement technologymechanicalRelease signallingoptiskRelease signallingakustiskRelease signallinghaptisk	Lever length without plug-in head [l ₁] Feedback	135 mm triggering
Release signallingoptiskRelease signallingakustiskRelease signallinghaptisk	Lever length without plug-in head [l ₁] Feedback Calibration	135 mm triggering O1
Release signallingakustiskRelease signallinghaptisk	Lever length without plug-in head [l ₁] Feedback Calibration Test certificate	135 mm triggering O1 Manufacturer's test certificate
Release signalling haptisk	Lever length without plug-in head [l ₁] Feedback Calibration Test certificate Data can be recorded	135 mm triggering O1 Manufacturer's test certificate no
	Lever length without plug-in head [l ₁] Feedback Calibration Test certificate Data can be recorded Measurement technology	135 mm triggering O1 Manufacturer's test certificate no mechanical
Series Slipper	Lever length without plug-in head [l ₁] Feedback Calibration Test certificate Data can be recorded Measurement technology Release signalling	135 mm triggering O1 Manufacturer's test certificate no mechanical optisk
	Lever length without plug-in head [l ₁] Feedback Calibration Test certificate Data can be recorded Measurement technology Release signalling Release signalling	135 mm triggering O1 Manufacturer's test certificate no mechanical optisk akustisk

Slipper functionyesQuick release/ quick-change functionnoMemory pointernoType of productTorque Wrench	Deflection function	no
Memory pointer no	Slipper function	yes
	Quick release/ quick-change function	no
Type of product Torque Wrench	Memory pointer	no
	Type of product	Torque Wrench

Services

Calibration Torque wrench maximum torque 400 Nm	018820 400
Labelling laser-etched Type	018940