

Garant
Torque wrench "Slipper" with scale, maximum torque: 5 Nm

Order data

Order number	657762 5
GTIN	4045197891617
Item class	61E

Description
Version:

The special slipping trigger mechanism **reliably prevents unintentional overtightening.**

Torque wrench with **micrometer scale for setting**, self-triggering. Hold in position at the end of the handle against inadvertent adjustment. With integral ratchet.

Units of measure: N·m.

Advantage:

Precision triggering mechanism facilitates working in inaccessible places.

Function:

On reaching the set torque value the wrench triggers a clearly detectable deflection and is then immediately ready for use again. The special trigger mechanism ensures that the set torque values are reliably achieved, **but not exceeded.**

Application:

For medium to larger batch productions.

Standard:

Geprüft nach DIN EN ISO 6789.

Accuracy:

±6 % of the set value.

Direction of tightening: For right-hand tightening

Torque measuring accuracy: ±6 %

Test certificate: Manufacturer's test certificate

Calibration: O1

Overall length L: 204 mm

Torque range: 1 - 5 Nm

Scale graduation, 1 graduation =: 0.05 Nm

Weight: 235 g

Square drive: 1/4 inch

Technical description

Direction of tightening	For right-hand tightening
Torque measuring accuracy	±6 %
Square drive	1/4 inch
Torque range	1 - 5 Nm
Weight	235 g
Display	analogue
maximum torque	5 Nm
Scale graduation, 1 graduation =	0.05 Nm
Reversible reading	Nm
Setting the trigger value	with adjustment scale
Overall length L	204 mm
Standard	DIN EN ISO 6789
Measurement process	Torque
Trigger principle	mechanical slip clutch
Lever length including factory calibration reference dimension [L ₃]	136.5 mm
Adjustable trigger value	adjustable
Lever length without plug-in head [L ₁]	135 mm
Feedback	triggering
Connection format	Push-through square drive (ratchet)
Calibration	O1
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	optisk
Release signalling	akustisk
Release signalling	haptisk
Series	Slipper

Deflection function	no
Slipper function	yes
Quick release/ quick-change function	no
Memory pointer	no
Type of product	Torque Wrench

Services

Calibration Torque wrench maximum torque 400 Nm	018820 400
Labelling laser-etched Type	018940