

**KANON**
**Minimal torque gauge, maximum torque: 6 cNm**

**Order data**

Order number	658800 6
GTIN	4582126965396
Item class	66F

**Description**
**Version:**

Accurate measuring instrument for the smallest torques. Easy-to-read scale with memory pointer on the top and additional scale on the side. **With 3-jaw steel chuck.**

**Application:**

For measuring the smallest torques (such as rotation and frictional resistances) and for controlled tightening of screws.

**Standard:**

Geprüft nach DIN EN ISO 6789.

**Note:**

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right- and left-hand tightening

Torque measuring accuracy:  $\pm 3\%$

Test certificate: Manufacturer's test certificate

Calibration: O3

Overall length L: 106 mm

Torque range: 5 - 60 mNm

Scale graduation, 1 graduation =: 1 mNm

Clamping chuck range: 1 - 6.5 mm

Ø: 43 mm

Weight: 290 g

**Technical description**

maximum torque	6 cNm
----------------	-------

Ø	43 mm
Clamping chuck range	1 - 6.5 mm
Weight	290 g
Torque range	5 - 60 mNm
Setting the trigger value	Memory pointer
Connection format	3-jaw chuck
Feedback	displaying
Display	analogue
Standard	DIN EN ISO 6789
Release signalling	visual
Series	SGK
Overall length L	106 mm
Measurement process	Torque
Scale graduation, 1 graduation =	1 mNm
Adjustable trigger value	non-adjustable
Reversible reading	Nm
Calibration	O3
Direction of tightening	For right- and left-hand tightening
Test certificate	Manufacturer's test certificate
Torque measuring accuracy	±3 %
Data can be recorded	no
Measurement technology	mechanical
Type of product	Torque Wrench