



Electronic torque screwdriver, maximum torque: 200 cNm



Order data

Order number	659010 200
GTIN	4571141275283
Item class	66F

Description

Version:

High precision electronic torque screwdriver with large easy-to-read display.

- **Display: Track mode and Peak mode.**
- **Memory capacity: Up to 1000 measured values.**
- **Interface: The saved measured data can be uploaded to a PC via the USB cable. Choice of 2 measurement modes:**
- **Screw tightening mode (specification of the required torque value, with warning limit).**
- **Inspection mode (specification of the upper and lower tolerance values). The respective measurement result is indicated by LEDs and a buzzer.**

Units of measure: cN·m, lbf·in, kgf·cm, ozf·in

Application:

Torque control; controlled tightening of screws in a single operation or for small batch production.

Standard:

Geprüft nach DIN EN ISO 6789.

Supplied with:

With lithium ion battery.

Optional extras:

See No. 65 5265 for USB data transmission cables.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right- and left-hand tightening

Torque measuring accuracy: ± 1 %

Interface: USB interface

Bit socket: F 6.3

Test certificate: Manufacturer's test certificate

Calibration: O3
 Overall length L: 230 mm
 Torque range: 40 - 200 cNm
 Resolution: 0.2 cNm
 Weight: 340 g

Technical description

Weight	340 g
maximum torque	200 cNm
Resolution	0.2 cNm
Torque measuring accuracy	±1 %
Torque range	40 - 200 cNm
Measurement process	Torque
Reversible reading	Nm
Reversible reading	lbf·in
Reversible reading	kgf·cm
Reversible reading	oz·in
Feedback	displaying
Release signalling	optisk
Release signalling	acoustic
Display	digital
Adjustable trigger value	adjustable
Setting the trigger value	digital, adjustable
Connection format	Bit holder 1/4 inch
Overall length L	230 mm
Calibration	O3
Direction of tightening	For right- and left-hand tightening
Test certificate	Manufacturer's test certificate
Interface	USB interface
Bit socket	F 6.3
Standard	DIN EN ISO 6789

Data can be recorded	yes
Measurement technology	electronic
Torque range	0.4 - 2 Nm
Battery capacity	2.5 Ah
Battery voltage	3.7 V
Number of rechargeable batteries contained	1
Type of rechargeable battery	Lithium-ion
Power supply	Rechargeable battery-powered
Type of product	Torque screwdriver

Services

Calibration Torque wrench both ends maximum torque 400/2 Nm	018821 400/2
---	--------------

Accessories

Data cable	655265
------------	--------