



## Electronic torque screwdriver, maximum torque: 400 cNm



### Order data

Order number	659010 400
GTIN	4571141275306
Item class	66F

### Description

#### Version:

High precision electronic torque screwdriver with large easy-to-read display.

- **Display: Track mode and Peak mode.**
- **Memory capacity: Up to 1000 measured values.**
- **Interface: The saved measured data can be uploaded to a PC via the USB cable. Choice of 2 measurement modes:**
- **Screw tightening mode (specification of the required torque value, with warning limit).**
- **Inspection mode (specification of the upper and lower tolerance values). The respective measurement result is indicated by LEDs and a buzzer.**

**Units of measure:** cN·m, lbf·in, kgf·cm, ozf·in

#### Application:

Torque control; controlled tightening of screws in a single operation or for small batch production.

#### Standard:

Geprüft nach DIN EN ISO 6789.

#### Supplied with:

With lithium ion battery.

#### Optional extras:

See No. 65 5265 for USB data transmission cables.

#### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right- and left-hand tightening

Torque measuring accuracy:  $\pm 1$  %

Interface: USB interface

Bit socket: F 6.3

Test certificate: Manufacturer's test certificate

Calibration: O3  
 Overall length L: 230 mm  
 Torque range: 80 - 400 cNm  
 Resolution: 0.5 cNm  
 Weight: 340 g

## Technical description

Weight	340 g
maximum torque	400 cNm
Resolution	0.5 cNm
Torque measuring accuracy	±1 %
Torque range	80 - 400 cNm
Feedback	displaying
Release signalling	optisk
Release signalling	acoustic
Overall length L	230 mm
Adjustable trigger value	adjustable
Measurement process	Torque
Reversible reading	Nm
Reversible reading	lbf·in
Reversible reading	kgf·cm
Reversible reading	oz·in
Display	digital
Connection format	Bit holder 1/4 inch
Setting the trigger value	digital, adjustable
Calibration	O3
Direction of tightening	For right- and left-hand tightening
Test certificate	Manufacturer's test certificate
Interface	USB interface
Bit socket	F 6.3
Standard	DIN EN ISO 6789

Data can be recorded	yes
Measurement technology	electronic
Torque range	0.8 - 4 Nm
Battery capacity	2.5 Ah
Battery voltage	3.7 V
Number of rechargeable batteries contained	1
Type of rechargeable battery	Lithium-ion
Power supply	Rechargeable battery-powered
Type of product	Torque screwdriver

## Services

Calibration Torque wrench both ends maximum torque 400/2 Nm	018821 400/2
---	--------------

## Accessories

Data cable	655265
------------	--------