



Electronic torque screwdriver, maximum torque: 200 cNm



Order data

Order number	659050 200
GTIN	4045197503879
Item class	62E

Description

Version:

Torque screwdriver with a flexible range of applications; with a 2-component handle, large display and quick-change coupling shank for bits. When the set value is reached, the torque screwdriver gives a clear visual and audible signal. 2 working modes are available - peak value display and tracking value display. Stores up to 50 values.

Units of measure: cN·m, lbf·in, kgf·cm

Application:

Torque control; controlled tightening of screws in a single operation or for small batch production.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right- and left-hand tightening

Torque measuring accuracy: $\pm 2\%$

Bit socket: F 6.3

Test certificate: Manufacturer's test certificate

Calibration: O3

Standard: DIN EN ISO 6789

Overall length L: 203 mm

Torque range: 40 - 200 cNm

Resolution: 0.1 cNm

Weight: 200 g

Technical description

Resolution	0.1 cNm
Weight	200 g
maximum torque	200 cNm
Torque measuring accuracy	±2 %
Torque range	40 - 200 cNm
Number of batteries contained	1
Release signalling	optisk
Release signalling	akustisk
Reversible reading	cNm
Reversible reading	lbf·in
Display	digital
Setting the trigger value	digital, adjustable
Measurement process	Torque
Connection format	Bit holder 1/4 inch
Overall length L	203 mm
Trigger principle	Electromechanical trigger
Feedback	displaying
Adjustable trigger value	adjustable
Calibration	O3
Direction of tightening	For right- and left-hand tightening
Test certificate	Manufacturer's test certificate
Bit socket	F 6.3
Standard	DIN EN ISO 6789
Data can be recorded	yes
Measurement technology	electronic
Battery type	LR3
Power supply	Battery-powered
Type of product	Torque screwdriver

Services

Calibration Torque wrench both ends maximum torque
400/2 Nm

018821 400/2

Accessories

Alkaline-manganese batteries International size LR3	081556 LR3
Alkaline manganese battery set International size LR3	081557 LR3
Coin-Driver, short Blade length 45 mm	664311 45
Battery compartment cover Type 1	655346 1
Alkaline manganese battery set International size LR3	081558 LR3
Coin-Driver Blade length 45 mm	664310 45
Alkaline-manganese batteries International size LR3	081561 LR3
Alkaline-manganese batteries International size LR3	081551 LR3