



“Torsiometer” torque screwdriver, maximum torque: 300 cNm



Order data

Order number	659200 300
GTIN	4018754118922
Item class	63A

Description

Version:

Ergonomic handle with torsion rod measuring device.
Scale with memory pointer for right hand threads.

Units of measurement: cN·m, lbf·in

Application:

For controlled single tightening of screws and for controlled measurements.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right- and left-hand tightening

Torque measuring accuracy: $\pm 4\%$

Bit socket: F 6.3

Calibration: O3

Torque measuring accuracy: $\pm 4\%$

Overall length L: 185 mm

Torque range: 60 - 300 cNm

Torque range: 6 - 26 lbf·in

Scale graduation, 1 graduation =: 10 cNm

Technical description

Display	analogue
maximum torque	300 cNm

Scale graduation, 1 graduation =	10 cNm
Torque measuring accuracy	±4 %
Bit socket	F 6.3
Torque range	60 - 300 cNm
Torque range	6 - 26 lbf·in
Trigger principle	mechanical short-travel release
Setting the trigger value	Memory pointer
Reversible reading	cNm
Reversible reading	lbf·in
Overall length L	185 mm
Feedback	displaying
Adjustable trigger value	non-adjustable
Measurement process	Torque
Weight	230 g
Standard	DIN EN ISO 6789
Connection format	Bit holder 1/4 inch
Series	TORSIOMETER 760
Calibration	O3
Direction of tightening	For right- and left-hand tightening
Data can be recorded	no
Measurement technology	mechanical
Release signalling	akustisk
Release signalling	haptisk
Torque fixed setting	no
Type of product	Torque screwdriver

Services

Calibration Torque wrench both ends maximum torque 400/2 Nm	018821 400/2
	018940

Labelling laser-etched Type
